

AMENDMENT NO. 1 MARCH 2021

TO

IS 16604 : 2017 AUTOMOTIVE VEHICLES — ARRANGEMENT OF FOOT CONTROLS OF VEHICLES — SPECIFICATION

(Page 1, clause 1) — Substitute the following for the existing clause:

‘1 SCOPE

This standard applies to vehicles of category M1 and L7-M with regard to the arrangement and mode of operation of the foot controls.’

(Page 1, clause 3.12) — Add the following new clause at the end of the clause:

‘3.13 Vehicles of category L7-M — A motor vehicle as defined in IS 14272.’

(Page 1, clause 4.1) – Substitute the following for the existing clause:

‘4.1 The foot controls shall be arranged in the following order from left to right, as observed from the driver’s seat, clutch pedal if any, service-brake pedal, accelerator pedals.’

(Page 1, clause 4.5) – Substitute the following for the existing clause:

‘4.5 The distance shown as ‘E’ in Fig. 3 and Fig. 4 of Annex B, between the contour points of the orthogonal projections on to plane ‘P’ of the accelerator-pedal and service-brake-pedal bearing surfaces shall be ≤ 100 mm and ≥ 50 mm.’

(Page 1, clause 4.6) – Substitute the following for the existing clause:

‘4.6 The distance ‘F’ in Fig. 4 between the orthogonal projections of the service-brake-pedal and the clutch-pedal bearing surfaces on to the reference plane ‘P’ shall be ≥ 50 mm.’

(Page 1, clause 4.7) – Substitute the following for the existing clause:

‘4.7 The distance ‘G’ in Fig. 4, between the contour points of the orthogonal projection of the clutch pedal on the plane ‘P’ and the intersection of the nearest wall with plane ‘P’ shall be ≥ 50 mm.’

(Page 2, clause 4.8) – Substitute the following for the existing clause:

‘4.8 The distances, respectively shown as ‘H’ and ‘J’ in Fig. 3 and Fig. 4, between the projection of the service-brake pedal on to the reference plane ‘P’ and the intersection of each of the walls with that plane shall be ≥ 130 mm to the right and ≥ 160 mm to the left for vehicles with three pedals (*see* Fig. 4) and ≥ 130 mm to the right and ≥ 120 mm to the left for vehicles with two pedals (*see* Fig. 3).’