

AMENDMENT NO. 1 DECEMBER 2021

TO

IS 16623 : 2017 PULSATED MOVEMENT MONOCABLE ROPEWAYS WITH FIXED GRIPS CODE OF PRACTICE

(Page 2, clause 4.2.8) — Substitute the following for the existing clause:

‘4.2.8 In closed/semi-enclosed vehicle installations, the height above ground shall not be greater than 25 m. However, this limit may be increased in small stretches not exceeding 10 percent of actual or slope length of the ropeway provided that the passenger safety is not compromised, but in no case shall the height above ground be greater than 40 m and in the case of accidental stoppage of the system, the rescue personnel shall be able to reach the vehicles and get the passengers to safety without being helped by the passengers.

4.2.8.1 In open vehicle installations (chair lifts, cabin lifts, etc), the maximum height of the lowest portion of the vehicle from the ground, measured in the most unfavourable conditions, shall not be more than 8 m. However, if the height above ground is less than 25 m and such length is less than 20 percent of the total ropeway, such installation will be allowed if a suitable designed and approved rescue cable pathway is provided below the vehicle where the vertical distance from cable path to the underside of the chair is kept within 25 m.

4.2.8.2 In a closed vehicle installation, the height above the ground may be more than 40 m if such length does not exceed 20 percent of the total system length provided a suitably designed and approved rescue cable pathway below the closed vehicle is provided. This 20 percent would be in addition to the relaxation given in 4.2.8 for height above the ground being between 25 m and 40 m in small stretches.

4.2.8.3 When the vertical clearance between the ground and the bottom of the loaded vehicle exceeds 40 m and a cable pathway below the vehicle is not provided in accordance with 4.2.8.2, a suitable rescue system with a rescue cabin shall be provided to bring the passengers to a safer place by transporting to a nearby trestle or station.’