

**AMENDMENT NO. 1 AUGUST 2019
TO
IS 16704 : 2018/ISO 16861 : 2015 PETROLEUM
PRODUCTS — FUELS (CLASS F) — SPECIFICATIONS OF
DIMETHYL ETHER (DME)**

(Second cover page, National Foreword, para 5) — This standard also makes a reference to the BIS Certification marking of the product. Details of which is given in National Annex A.

NATIONAL ANNEX A
(National Foreword)

A-1 PACKING AND MARKING

A-1.1 Packing

The material shall be packed in suitable cylinders/ containers as agreed to between the purchaser and the supplier and subject to the requirements prescribed by statutory authorities.

A-1.2 Marking

The cylinders/containers shall be marked as prescribed by statutory authorities from time to time. They shall bear the labels marked with the following information:

- a) Name and type of the material;
- b) Mass of the material in the container, in kg;
- c) Maximum vapour pressure; and
- d) Manufacturer's name and trade-mark, if any

NOTE — Each consignment shall be designated by its maximum vapor pressure in kPa at 40°C and shall not exceed 16.87 kg/cm² at 65°C for transportation through road tank trucks.

A-1.2.1 Each cylinder/container shall also be marked with the caution label 'FLAMMABLE' together with the corresponding symbol for labeling dangerous goods [see Fig.18 of IS 1260 (Part 1)].

Amendment No. 1 to IS 16704 : 2018/ISO 16861 : 2015

A-2 BIS CERTIFICATION MARKING

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the standard mark.

(PCD 03)

Publication Unit, BIS, New Delhi, India