

AMENDMENT NO. 1 APRIL 2021
TO
IS 16723 : 2020 COMBINATION LOCK — SPECIFICATION
(First Revision)

(Page 2, clause 6.2) — Substitute the following for existing:

Lock mounting holes may have standard footprint, as per the Fig. 2 so that lock can be retrofitted with any international make Combination lock.

(Page 3, clause 9.2.3) — Substitute the following for existing:

‘For Class I and Class II — A three wheel combination Lock shall not open when the dial is turned more than one full and 1/4th dial graduation on either side of the set number for any of the wheels. A four wheel combination lock shall not open when the dial is turned more than one full and 1/2 graduations mark on either side of the set number for any of the wheels.

For Class III — A three wheel combination Lock shall not open when the dial is turned more than one full dial graduation on either side of the set number for any of the wheels. A four wheel combination lock shall not open when the dial is turned more than one full and 1/4 graduations mark on either side of the set number for any of the wheels.’

(Page 4, clause 9.2.4) — Substitute the following for existing:

For Class I and Class II — the test for three wheel combination lock is to be conducted by applying the combination one number at a time in the following manner.

- a) Dial the combination with the first number more than one full and 1/4th graduation lower than set combination and second and third number as they are set.

Price Group 1

- b) Dial the combination with the first number more than one full and 1/4th graduation higher than set combination and second and third number as they are set.
- c) Dial the combination with the second number more than one full and 1/4th graduation lower than set combination and first and third number as they are set.
- d) Dial the combination with the second number more than one full and 1/4th graduation higher than set combination and first and third number as they are set.
- e) Dial the combination with the third number more than one full and 1/4th graduation lower than set combination and first and second number as they are set.
- f) Dial the combination with the second number more than one full and 1/4th graduation higher than set combination and first and third number as they are set.

(Page 4, clause 9.2.6) — Substitute the following for existing:

‘Class III

- a) Dial the combination with the first number more than one full graduation lower than set combination and second and third number as they are set.
- b) Dial the combination with the first number more than one full graduation higher than set combination and second and third number as they are set.
- c) Dial the combination with the second number more than one full graduation lower than set combination and first and third number as they are set.
- d) Dial the combination with the second number more than one full graduation higher than set combination and first and third number as they are set.
- e) Dial the combination with the third number more than one full graduation lower than set combination and first and second number as they are set.
- f) Dial the combination with the second number more than one full graduation higher than set combination and first and third number as they are set.’

(Page 4, clause **9.2.6**) — Insert the following new clauses:

9.2.7 A four wheel lock is to be tested in the same sequence as described in **9.2.6** except that the change is to be more than 1 full and 1/4th dial graduation lower or higher.

9.2.8 If the lock opens as a result of any of these attempts, the trial is to be repeated with the combination numbers changed 1/4th dial of a graduation more. The lock shall not open on that trial.'