

AMENDMENT NO. 1 APRIL 2022

TO

IS 16988 : 2018 COMPRESSED NATURAL GAS CYLINDER VALVE INTEGRATED WITH SOLENOID OPERATION (REMOTELY CONTROLLED) FOR AUTOMOTIVE USE — SPECIFICATION

(Page 13, clause 8.2.2) — Insert the following new clause:

‘8.3 Parallel threads on the valve stem with cylinder neck dimensions as per IS 3224.’

(Page 13, clause 9.1.1) — Substitute ‘The dimension of the valve outlet having internal threads shall be in conformity with the details given in Table 10 outlet numbers 21, 21A and 21B.’ for ‘The dimension of the valve outlet having internal threads shall be in conformity with the details given in Table 10 outlet numbers 21 and 21a.’

(Page 13, Table 10 and foot note) — Substitute the following for the existing:

‘Table 10 Details of Valves

(Clause 9.1.1)

All dimensions are in millimeters


Sl No.	Designation of Screw Thread Outlet	Pitch	Outlet No.
(1)	(2)	(3)	(4)
i)	G5/8-14 TPI-LH	1.814	21
ii)	INT-M12 × 1P-RH	1.00	21A
iii)	1/4" NGT/1/4" NPT-RH	1.411	21B

NOTES:

1 For 1/4" NPT threads, Gauging of these threads shall be done as gauging of 1/4" NGT as per IS 15894.

2 G = fastening pipe thread as per IS 2643, symbol A indicates external thread of class A. Absence of A indicates internal thread, M = metric thread and Int = internal thread’

(Page 14, outlet no 21A) — Insert the following outlet figure after outlet no. 21A:



VALVE OUTLET

Threads INT. 1/4"NPT
or 1/4" NGT
Thraed per inch 18
Pitch of Thread 1.411

All Dimensions in millimeters.

OUTLET No. 21B OUTLET CONNECTION FOR COMPRESSED NATUREAL GAS