

AMENDMENT NO. 2 DECEMBER 2023

TO

IS 1293 : 2019 PLUGS AND SOCKETS-OUTLETS FOR HOUSEHOLD AND SIMILAR PURPOSES OF RATED VOLTAGE UP TO AND INCLUDING 250 V AND RATED CURRENT UP TO AND INCLUDING 16A — SPECIFICATION

(*Fourth Revision*)

(Page 1, *clause 2*) — Insert the following at the end:

‘IS 17048 : 2019 Halogen Free Flame Retardant (HFFR) cables for working voltages upto and including 1 100 V’.

(Page 8, *clause 5.2, para 2*) — Substitute the following for the existing:

‘Non-rewireable accessories are tested with the type and size of flexible/rigid cable as delivered; those not incorporated in a cord set or a cord extension set or which are not a component of equipment shall be provided for testing, with at least 1 m of flexible or rigid cable, wherever applicable, of relevant specification.’

[Page 9, *Table 2 (see also amendment No. 1)*] — Substitute the following for the existing table:

Table 2 Types and Ratings

(*Clause 6.1*)

SI No.	Type	Rated Current
(1)	(2)	A (3)
i)	2P (non-rewireable plugs only)	2.5
ii)	2P (Socket & non-rewireable plugs only), 2P + 	6
iii)	2P (non-rewireable plugs only), 2P + 	16
iv)	2P +  (combined socket-outlets only)	6/16

NOTE — Types and ratings other than that specified in Table 2 are not permitted.

Price Group 1

Amendment No. 2 to IS 1293 : 2019

[Page 40, Table 17, (see also amendment No. 1)] — Substitute the following for the existing:

Table 17 External Dimensions of Flexible/Rigid Cables to be Accommodated by Cord Anchorage

(Clauses 16.2.1, 17.1.1, 17.1.2 and 23.2)

Sl No.	Rating of Accessory	Number of Poles	Types of Flexible/Rigid Cable (Cable References)	Number of Conductor Strand Nominal Cross Sectional Area mm ²	Limits of External Dimensions for Flexible/Rigid Cables mm	
					Minimum	Maximum
(1)	(2)	(3)	(4)	(5)	(6)	(7)
(i)	6 A Up to and including 250 V	2	IS 694	2 × 0.75	2.7 × 5.4	3.2 × 6.4
				2 × 0.75	3.8 × 6.0	5.2 × 7.6
			IS 17048	2 × 0.75	2.7 × 5.4	3.2 × 6.4
				2 × 0.75	3.8 × 6.0	5.2 × 7.6
(ii)	6 A Up to and including 250 V	2	IS 694	2 × 0.75	2.7 × 5.4	3.2 × 6.4
				2 × 1	6.4	8.0
		3		3 × 0.75	6.4	8.4
				3 × 1		
		2	IS 17048	2 × 0.75	2.7 × 5.4	3.2 × 6.4
				2 × 1	6.4	8.0
(iii)	Above 6 A Up to and including 16 A, Up to and including 250 V	2	IS 694	3 × 0.75		
				3 × 1		
		3		3 × 0.75		
				3 × 1.5		
		2	IS 17048	2 × 0.75	2.7 × 5.4	3.2 × 6.4
				2 × 1.5	7.4	9.0
		3		3 × 0.75		
				3 × 1.5		

(Page 55, clause 23.3, para 3) — Substitute the following for the existing:

‘Compliance is checked by inspection, by measurement and by checking that the flexible/rigid cables are in accordance with the relevant parts of either IS 694 or IS 9968 (Part 1) or IS 17048 as applicable.’