

AMENDMENT NO. 2 JUNE 2026
TO
IS 1460 : 2025 AUTOMOTIVE DIESEL FUEL — SPECIFICATION
(Seventh Revision)

(Second cover page, Foreword, para 12) — Substitute the following for the existing:

‘For test methods at SI No. (xii), (xvii), (xviii), and (xix) in Table 1 and SI No. (xii), (xviii), (xix), and (xx) in Table 2, EN standards are referred since Indian Standards are not available for those tests. Those will be updated with Indian standards, once developed and approved by respective Sectional Committee. Also, alternate test methods are provided below for few test parameters considering the request of certifying test laboratories, availability of relevant equipment, and ease of product certification. In case of dispute, the referee methods prescribed in Table 1 and Table 2 shall be followed:’

[Second cover page, Foreword, para 12, Table, row 20, col (2)] — Insert ‘ISO 12156-1’ after ‘ASTM D6079’.

(Page 1, clause 3.2) — Insert the following new clause after 3.2:

‘3.3 Winter Grade Diesel

The specification for automotive diesel winter grade is provided in Table 2. This specification can be referred for automotive diesel certified and retailed for automotive and stationary diesel engine applications and it is applicable only for usage in the states of Himachal Pradesh, Jammu-Kashmir, Leh, Ladakh, Sikkim, and Arunachal Pradesh.’

(Page 3, Table 1) – Insert the following new Table after Table 1:

‘Table 2 Requirement for Automotive Diesel Fuel - Winter Grade

(Clause 3.3 and Foreword)

SI No.	Characteristic	Requirement	Method of Test, Ref to Parts of IS 1448/ISO/EN/Annex
(1)	(2)	(3)	(4)
i)	Appearance	Clear, bright and free from sediments, suspended matter and undissolved water at normal ambient fuel temperature	Visual
ii)	Total Acid Number (TAN), mg of KOH/g, <i>Max</i>	0.20	(Part 2) ⁷⁾
iii)	Ash, percent by mass, <i>Max</i>	0.01	(Part 4/Sec 1) ⁷⁾
iv)	Carbon residue, on 10 percent residue ¹⁾ , percent by mass, <i>Max</i>	0.30	(Part 8) ⁷⁾ / (Part 189)
v)	Cetane number ²⁾ , <i>Min</i>	51	(Part 9) ⁷⁾
vi)	Cetane index ²⁾ , <i>Min</i>	46	(Part 174) ⁷⁾
vii)	Pour point, °C, <i>Max</i>	-30	(Part 10/Sec 2) ⁷⁾
viii)	Copper strip corrosion for 3 h at 50 °C, <i>Max</i>	Class 1	(Part 15) ⁷⁾
ix)	Distillation: 10 percent v/v recovery, °C, <i>Min</i>	180	(Part 18) ⁷⁾ / ISO 3405 / ISO 3924

Amendment No. 2 to IS 1460 : 2025

SI No.	Characteristic	Requirement	Method of Test, Ref to Parts of IS 1448/ISO/EN/Annex
(1)	(2)	(3)	(4)
	95 percent v/v recovery, °C, <i>Max</i>	360	
x)	Flash point, Abel ³⁾ , °C, <i>Min</i>	35	(Part 20) ⁷⁾
xi)	Kinematic viscosity, mm ² /s, at 40 °C	1.5 to 4.0	(Part 25/Sec 1) ⁷⁾ / (Part 186)
xii)	Total contamination, mg/kg, <i>Max</i>	24	EN 12662 ⁷⁾
xiii)	Density ⁴⁾ at 15 °C, kg/m ³	800 to 845	(Part 16) ⁷⁾ / (Part 32) / (Part 167)
xiv)	Total sulphur, mg/kg, <i>Max</i>	10	(Part 160) ⁷⁾ / (Part 34) / (Part 161) / (Part 159)
xv)	Water content, mg/kg, <i>Max</i>	200	(Part 182) ⁷⁾
xvi)	Cold Filter Plugging Point (CFPP), °C, <i>Max</i>	-20	(Part 110) ⁷⁾
xvii)	Cloud point, °C, <i>Max</i>	-10	(Part 10/Sec 1)
xviii)	Oxidation stability ⁵⁾ , g/m ³ , <i>Max</i>	25	(Part 154) ⁷⁾
	OR		
	Oxidation stability ⁵⁾ , minutes, <i>Min</i>	60	EN 16091 ¹¹⁾
xix)	Oxidation stability (for diesel fuel having FAME content of above 2 percent v/v), hours, <i>Min</i>	20	EN 15751 ⁷⁾
	OR		
	Oxidation stability (for diesel fuel having FAME content of above 2 percent v/v), minutes, <i>Min</i>	60	EN 16091
xx)	Polycyclic Aromatic Hydrocarbon (PAH), percent by mass, <i>Max</i>	8	EN 12916 ⁷⁾
xxi)	Lubricity, wear scar diameter ¹²⁾ (wsd) at 60 °C, µm, <i>Max</i>	460	(Part 149) ⁷⁾
xxii)	FAME content ⁶⁾ , percent v/v, <i>Max</i>	7.0	Annex C ⁷⁾

NOTES

¹⁾ This limit is applicable prior to addition of ignition improvers, if used. In case a value exceeding the limit is obtained on finished fuels in the market, ASTM D4046/ISO 13759 shall be used to establish the presence of nitrate containing compound. In such case the present limit for carbon residue cannot be applied. However, the use of ignition improver does not exempt the manufacturer from meeting this requirement prior to the addition of the additive.

²⁾ Cetane number and cetane index relaxation and time frame, if any, for fuel processed from Assam crude, may be guided by the notifications issued by Government of India, from time to time.

³⁾ Whenever abel flash point exceeds 70 °C by IS 1448 (Part 20)/IP 170, PMCC flash point by IS 1448 (Part 21) is to be used.

⁴⁾ Density range relaxation and time frame, if any, for fuel processed from Assam Crude, may be guided by the notifications issued by Government of India, from time to time.

⁵⁾ This test shall be carried out only at the refinery or manufacturer's end.

⁶⁾ Required if blended with biodiesel. Biodiesel shall conform to IS 15607.

⁷⁾ In case of dispute, this method shall be the referee test method.

⁸⁾ No external addition of chlorine-based materials and metallic additives are allowed.

Amendment No. 2 to IS 1460 : 2025

⁹⁾ Fuel should be free from chloride or chlorinated materials and metallic additives during manufacturing, storage, handling, dispatch and delivery. In case of any dispute raised by consumer on chloride content in the fuel (above 10 mg/kg), representative fuel sample collected at the point of delivery or point of dispensing can be tested by wavelength dispersive X-Ray fluorescence (WDXRF) or energy dispersive X-Ray fluorescence (EDXRF) or micro coulometric technique by a competent testing laboratory, as applicable.

¹⁰⁾ All test methods referred to in this standard include a precision statement. The interpretation of results based on test method/ precision shall be used whenever applicable. In case of dispute the procedure described in IS 17315 (Part 2) shall be used.

¹¹⁾ EN 16091 may be used for determination of oxidation stability of automotive diesel without addition of cetane improver. IS 1448 (Part 154) is the referee method and shall be used in case of dispute.

¹²⁾ Lubricity wear scar diameter limit shall be ensured by necessary dosage of lubricity additive.’

(Page 4, Annex A) – Insert the following new row *after* ISO 3405 : 2019:

ISO 3924 : 2019	Petroleum products — Determination of boiling range distribution — Gas chromatography method
-----------------	--