

AMENDMENT NO. 1 AUGUST 1982
TO
IS : 1498-1970 CLASSIFICATION AND
IDENTIFICATION OF SOILS FOR GENERAL
ENGINEERING PURPOSES

(First Revision)

Addenda

(Page 13, clause 3.8) — Add the following new clause after 3.8:

‘3.9 Degree of Expansion — Fine grained soils depending upon the presence of clay mineral exhibit low to very high degree of expansion. Based upon Atterberg’s limits and free swell of the soils the degree of expansion and degree of severity for soils is shown in Table 8.’

[Page 14, col 5 against Sl No. (ii)] — Add the following new matter at the end:

‘ Coarse: 75 micron to 7.5 micron

Fine: 7.5 micron to 2 micron’

(Page 21, Table 5, Note 4) — Add the following new note after note 4:

‘NOTE 5 — In most of the expansive soils, the CBR values after soaking are often found to be less than 2. The thickness of the pavements for such small values turn out to extremely high and impracticable. A minimum CBR value of 2 is recommended for use for design purposes in such soil.’

(Page 23, Table 7) — Add the following new table after Table 7:

**TABLE 8 SHOWING THE DEGREE OF EXPANSION OF FINE
GRADED SOILS**

(Clause 3.9)

LIQUID LIMIT (WL)	PLASTICITY INDEX (IP)	SHRINKAGE INDEX (IS)	FREE SWELL (PERCENT)	DEGREE OF EXPANSION	DEGREE OF SEVERITY
20-35	< 12	< 15	< 50	Low	Non-critical
35-50	12-23	15-30	50-100	Medium	Marginal
50-70	23-32	30-60	100-200	High	Critical
70-90	> 32	> 60	> 200	Very High	Severe

(BDC 29)

Printed at Simco Printing Press, Delhi, India