

AMENDMENT NO. 3 MARCH 2006
TO
IS 3589 : 2001 STEEL PIPES FOR WATER
AND SEWAGE (168.3 TO 2540 mm OUTSIDE
DIAMETER) — SPECIFICATION

(Third Revision)

(Title & General) — Delete the word 'gas' wherever it appears in the standard.

Substitute '168.3 mm outside diameter and above' for '168.3 to 2 032 mm outside diameter' wherever it appears.

(Page 2, clause 7.3) — Insert the following new clause after 7.3:

'7.3.1 Whenever agreed between the manufacturer and the purchaser, a maximum of two circumferential welds are permissible to make a full length. The tests for such tubes shall be mutually agreed. Minimum length of jointed tubes shall not be less than 1.5 meter.'

(Page 6, Table 5) — The mass of pipes of following sizes for the specified thickness and OD may be modified as given below:

Sl No.	Outside Diameter	Thickness	Mass
	mm	mm	kg/m
1	168.3	3.2	13.0
2	273	6.3	41.4
3	323.9	4.0	31.6
4	610	5.8	86.4
5	813	18	352.9
6	1 067	10	260.7
7	1 829	14.2	635.5

Amend No. 3 to IS 3589 : 2001

(*Page 9, Annex A, clause A-2*) — Insert the following sentence at the end of para:

‘Alternatively 4 mm wire with a pitch of 50 mm may be wrapped over lined steel cylinder pipe with the tension of 50 to 65 MPa.’

(*Page 13, Annex B, clause B-1.1, line 4*) — Substitute the words ‘coal tar’ for ‘coal rat’.

(MTD 19)