

AMENDMENT NO. 1 JUNE 2026
TO
IS 3843 : 1995 STEEL BACK FLAP HINGES — SPECIFICATION
(Second Revision)

(Page 1, clause 3) — Substitute the following for the existing:

‘3 CONSTRUCTION AND TYPE

3.1 Based on construction, steel back flap hinges shall be classified as follows:

- a) Plain joint hinges; and
- b) Washer hinges.

3.2 Further, steel back flap hinges shall be of the following two types (*see* Fig. 1):

- a) Light weight hinges (*see* Table 1); and
- b) Heavy weight hinges (*see* Table 2).’

(Page 1, clause 4) — Substitute the following for the existing:

‘4 MATERIALS

4.1 Materials used for the manufacture of steel back flap hinges shall comply with the requirements given in Indian Standards mentioned in col (4) of Table 3.

4.2 Other steel materials may also be used as agreed between the manufacturer and the purchaser. However, the Indian Standard and grade of that material shall be declared by the manufacturer.’

(Page 1, clause 5.2) — Insert the following at the end:

‘5.3 In each type of steel back flap hinges (*see* 3.2), any other dimensions, that is, combination of length, breadth, thickness of flap and diameter of pin, may also be manufactured as agreed between the manufacturer and the purchaser. However, the thickness of the flap and the diameter of the pin shall not be less than the nearest higher size of the hinges in the same type. Also, in such cases, the minimum width of the knuckle (*E*), number of screw holes, their sizes and positions shall be declared by the manufacturer.’

5.3.1 The tolerances on any other dimensions shall be as follows:

- a) Length (*A*): ± 0.5 mm; and
- b) Breadth (*B*): ± 1.0 mm.

5.3.2 For thickness of flap, specified as ‘*C Min*’ in Table 1 and Table 2, a manufacturing tolerance of - 0.05 mm shall be allowed on the finished product with respect to the specified value.

NOTE — For example, in Table 1, where the thickness of flap (*C Min.*) is specified as 1.6 mm for size 20, the minimum acceptable thickness on the finished product shall be 1.55 mm.’

(Page 1, clause 6.2) — Insert the following at the end:

‘In case of welded hinges, the single pin shall be used and cover a minimum of 90 percent of the length of the hinge.’

(Page 2, Table 1, clause reference) — Substitute ‘(Clauses 3.2, 5.1, 5.3.2, 6.2, 6.4.2 and 6.4.3)’ for ‘(Clauses 3, 5.1, 6.2, 6.4.2 and 6.4.3)’.

[Page 2, Table 1, col (4), heading] — Substitute ‘*C Min*’ for ‘*C*’.

Amendment No. 1 to IS 3843 : 1995

[Page 2, Table 1, col (4), all the rows of the table] — Delete ‘ ± 0.05 ’.

[Page 2, Table 1, col (5), heading] — Substitute ‘*D Min*’ for ‘*D*’.

[Page 2, Table 1, col (5), first eight rows] — Delete ‘ ± 0.05 ’.

[Page 2, Table 1, col (5), last two rows] — Delete ‘ ± 0.06 ’.

[Page 2, Table 1, col (6), heading] — Substitute ‘*E Min*’ for ‘*E*’.

[Page 2, Table 1, col (6), all the rows of the table] — Delete ‘ ± 0.5 ’.

[Page 2, Table 2, clause reference] — Substitute ‘(Clauses 3.2, 5.1, 5.3.2 6.2, 6.4.2 and 6.4.3)’ for ‘(Clauses 3, 5.1, 6.2, 6.4.2 and 6.4.3)’.

[Page 2, Table 2, col (4), heading] — Substitute ‘*C Min*’ for ‘*C*’.

[Page 2, Table 2, col (4), all the rows of the table] — Delete ‘ ± 0.06 ’.

[Page 2, Table 2, col (5), heading] — Substitute ‘*D Min*’ for ‘*D*’.

[Page 2, Table 2, col (5), all the rows of the table] — Delete ‘ ± 0.05 ’.

[Page 2, Table 2, col (6), heading] — Substitute ‘*E Min*’ for ‘*E*’.

[Page 2, Table 2, col (6), all the rows of the table] — Delete ‘ ± 0.5 ’.

(Page 2, Table 3) — Substitute the following for the existing:

‘Table 3 Requirements of Materials for Steel Back Flap Hinges

(Clause 4.1)

SI No.	Part	Material	Refernces to IS
(1)	(2)	(3)	(4)
i)	Flap	Mild steel	IS 2062 (Part 1), IS 2062 (Part 2), IS 1079, IS 513 (Part 1), IS 10748, IS 11513 and IS 5986
		Stainless steel	IS 6911
ii)	Pin	Mild steel wire	IS 280 and IS 7887
		Stainless steel wire	IS 6528

(Page 3, clause 7) — Substitute the following for the existing:

‘7 CORROSION RESISTANCE AND FINISH

7.1 Unless otherwise specified, hinges shall be either oxidised or naturally finished bright with smooth surface and when tested for neutral salt spray test as per IS 5528 for following durations, shall pass the corrosion resistance requirements of respective grades:

- Grade 0 — No requirement;
- Grade 1 — Mild resistance, up to 24 h;
- Grade 2 — Moderate resistance, up to 48 h;
- Grade 3 — High resistance, up to 96 h; and
- Grade 4 — Very high resistance, up to 240 h.

Amendment No. 1 to IS 3843 : 1995

7.2 After testing, the hinge sample(s) shall not show any corrosion on the visible surfaces.

7.3 Hinges of other finishes may also be supplied by the manufacturer subject to conformity with the corrosion resistance requirements.’

(Page 3, clause 9) — Substitute the following for the existing:

‘9 PACKING

9.1 Hinges shall be packed in cardboard boxes or in any other packing which avoids damages to the product and injury to the purchaser.

9.2 Each package shall be marked showing the following particulars:

- a) Manufacturer’s name or brand name or trade name;
- b) Construction (*see 3.1*) and type of hinges (*see 3.2*);
- c) Dimensions of hinges, that is, length, breadth and thickness of flap;
- d) Corrosion resistance grade (*see 7.1*);
- e) Grade and IS of material (both flap and pin); and
- f) Quantity of hinges.’

(Page 4, Annex A) — Substitute the following for the existing:

<i>‘IS No.</i>	<i>Title</i>
IS 280 : 2006	Mild steel wire for general engineering purposes (<i>fourth revision</i>)
IS 513 (Part 1) : 2016	Cold reduced carbon steel sheet and strip (<i>sixth revision</i>)
IS 1079 : 2017	Hot rolled carbon steel sheet, plate and strip — Specification (<i>seventh revision</i>)
IS 2062	Structural steel:
(Part 1) : 2025	Hot rolled medium and high tensile steel (<i>eighth revision</i>)
(Part 2) : 2026	Hot rolled quenched and tempered steel plates, sheets, strips and wide flats
IS 4905 : 2015/ ISO 24153 : 2009	Random sampling and randomization procedures (<i>first revision</i>)
IS 5528 : 2024/ ISO 9227 : 2022	Corrosion tests in artificial atmospheres — Salt spray tests (<i>second revision</i>)
IS 5986 : 2017	Hot rolled steel sheet, plate and strip for forming and flanging purposes — Specification (<i>fourth revision</i>)
IS 6528 : 2024	Stainless steel wire — Specification (<i>second revision</i>)
IS 6760 : 1972	Specification for slotted countersunk head wood screws
IS 6911 : 2026	Stainless steel plate, sheet and strip — Specification (<i>third revision</i>)
IS 7887 : 1992	Mild steel wire rod for general engineering purposes — Specification (<i>first revision</i>)
IS 10748 : 2025	Hot-rolled steel plates, sheets and strips for welded tubes and pipes — Specification (<i>third revision</i>)
IS 11513 : 2017	Hot rolled carbon steel strip for cold rolling purposes — Specification (<i>second revision</i>)’