

**AMENDMENT NO. 1 MAY 2026**  
**TO**  
**IS 3025 (Part 23) : 2023 METHODS OF SAMPLING AND TEST (PHYSICAL AND**  
**CHEMICAL) FOR WATER AND WASTEWATER**  
**PART 23 ALKALINITY**  
*( Second Revision )*

*(Page 2, clause 10.1, line 11)* — Substitute ‘pH 4.5’ for ‘pH 3.7’.

*(Page 2, clause 10.2, line 3)* — Substitute ‘pH 4.5’ for ‘pH 3.7’.

*(Page 2, clause 11.1, line 3)* — Substitute the following for existing:

$$\text{‘Phenolphthalein alkalinity (as mg/l of CaCO}_3\text{)} = \frac{A \times N \times 50\,000}{V}$$

$$\text{Phenolphthalein alkalinity (as mg/l of HCO}_3\text{)} = \frac{A \times N \times 61\,000}{V}$$

$$\text{Total alkalinity (as mg/l CaCO}_3\text{)} = \frac{(A+B) \times N \times 50\,000}{V}$$

$$\text{Total alkalinity (as mg/l HCO}_3\text{)} = \frac{(A+B) \times N \times 61\,000}{V}$$

where

*A* = volume, in ml, of standard sulphuric acid used to titrate to pH 8.3;

*B* = volume, in ml, of standard sulphuric acid used to titrate from pH 8.3 to pH 4.5;

*N* = normality of acid used; and

*V* = volume, in ml, of sample taken for test’.

*(Page 3, Table 1)* — Substitute ‘Total Alkalinity (T)’ for ‘Total Alkalinity (1)’.

(CHD 36)

**Price Group 1**  
Publication, BIS, New Delhi