

AMENDMENT NO. 1 JUNE 2006
TO
IS 3028 : 1998 AUTOMOTIVE VEHICLES —
NOISE EMITTED BY MOVING VEHICLES —
METHOD OF MEASUREMENT

(*Second Revision*)

(*Page 3, clause 6.11*) — Substitute the following for the existing text:

‘The test shall be carried out on fully built vehicle. In case of a drive away chassis, the test shall be conducted as per declaration of vehicle manufacturer for recommended kerb weight and with the test driver. In absence of this data, drive away chassis may be loaded applying the cab/body weight allowance as per Table 1 below:

Table 1 Load Schedule

Sl No.	GVW Range, kg	Allowance in Weight	
		Load Body Weight, kg	Cab Body Weight, kg
1	Up to 3 000	120	400
2	Above 3 000 but below 4 000	200	400
3	Above 4 000 but below 6 000	400	400
4	Above 6 000 but below 10 000	700	400
5	Above 10 000	1 000	400

[*Page 5, clause 9.4.1.1(b), line 11 onwards*] — Substitute the following for the existing:

‘If x/n does not correspond to a whole number, the next higher gear ratio (‘higher gear ratio’ means the next lower numerical ratio giving higher approach speed) shall be used. Shifting the gears from x/n must be terminated in the gear X where the engine speed (S), at which the engine develops its rated maximum power, is for the last time reached when passing the line BB ’.

Example: There are 16 forward ratios for drive train having a transmission for 8 gears and an auxiliary transmission with two gears. If the engine has 230 kW then $(x/n) = (8 \times 2)/3 = 16/3 = 5\frac{1}{3}$. The initial test gear ratio is 6th (includes the gears from both the main transmission and auxiliary which is 6th out of the 16 total gear ratios), with the next gear ratio is 7th up to range X .’

(*Page 6, clause 10.2.1, first line*) — Substitute ‘For three wheeler and four wheeler vehicles’ for ‘For vehicles’.

(TED 4)