

AMENDMENT NO. 2 JULY 2017
TO
IS 3196 (PART 1) : 2013 WELDED LOW CARBON STEEL
GAS CYLINDER EXCEEDING 5 LITRES WATER
CAPACITY FOR LOW PRESSURE LIQUEFIABLE
GASES

PART 1 CYLINDERS FOR LIQUEFIED PETROLEUM GAS (LPG) —
SPECIFICATION

(Sixth Revision)

[Page 3, clause 6.2.3, equation 1] — Substitute ' $t_{e \text{ Minimum}}$ ' for ' $t_{e \text{ Min}}$ '.

[Page 3, clause 6.2.3, equation 2] — Substitute ' $t_{e \text{ Minimum}}$ ' for ' $t_{e \text{ Min}}$ '.

[Page 3, clause 6.2.3, equation 3] — Substitute ' $t_{e \text{ Minimum}}$ ' for ' $t_{e \text{ Min}}$ '.

(Page 5, clause 9.3.1) — Insert the following sentence at the end of clause:

‘The shroud may be metallic or non-metallic as approved by statutory authority. Arrangement for fixing shroud on the cylinder shall be made of compatible steel.’

(Page 5, clause 9.3.2) — Substitute the following for the existing clause:

‘9.3.2 The protective metal ring or grill shall be welded or fixed to the upper end of the cylinder concentric with the neck. The eccentricity of the welded metal ring or grill with respect to the valve pad/bung shall not be more than 1 percent of the nominal diameter of cylinder subject to a maximum of 3 mm.’