

AMENDMENT NO. 3 DECEMBER 1983
TO
IS : 5698-1970 SPECIFICATION FOR ROTARY FORM RELIEVED
GEAR CUTTERS FOR SPUR AND HELICAL GEARS

Alterations

(*Page 2, clause 4, Table*) — Substitute the table on page 2 for the existing table:

(*Page 7, Cutter No. 6, column X, last entry*) — Substitute ' 158·877 ' for ' 153·257 '

All dimensions in millimetres.

Module, m		4 h16	D h7	h*	nt	Width b for Cutter Numbers																		
Pre-ferred	Choice 2					1	1½	2	2½	3	3½	4	4½	5	5½	6	6½	7	7½	8				
1	—	45	16	2.25	16	4.5	—	4.5	—	4	—	4	—	4	—	4	—	4	—	4	—	4	—	4
—	1.125	45	16	2.53	16	4.5	—	4.5	—	4	—	4	—	4	—	4	—	4	—	4	—	4	—	4
—	1.25	50	16	2.81	14	5	—	5	—	4.5	—	4.5	—	4.5	—	4.5	—	4.5	—	4.5	—	4.5	—	4.5
—	1.375	50	16	3.09	14	5.5	—	5.5	—	5	—	5	—	5	—	5	—	5	—	5	—	5	—	5
1.5	—	55	22	3.38	14	6	—	6	—	5.5	—	5.5	—	5.5	—	5.5	—	5.5	—	5.5	—	5.5	—	5.5
—	1.75	55	22	3.94	14	7	—	6.5	—	6.5	—	6.5	—	6.5	—	6	—	6.5	—	6.5	—	6.5	—	6.5
2	—	63	22	4.50	12	8	—	7.5	—	7.5	—	7.5	—	7.5	—	7	—	7.5	—	7.5	—	7	—	7
—	2.25	63	22	5.06	12	9	—	8.5	—	8	—	8	—	8	—	8	—	8	—	8	—	8	—	8
2.5	—	70	22	5.63	12	9.5	—	9.5	—	9	—	9	—	8.5	—	8.5	—	8.5	—	8.5	—	8.5	—	8.5
—	2.75	70	22	6.19	12	10.5	—	10	—	10	—	10	—	9.5	—	9.5	—	9	—	9.5	—	9	—	9
3	—	80	27	6.75	12	11.5	—	11	—	10.5	—	10.5	—	10.5	—	10.5	—	10.5	—	10.5	—	10.5	—	10.5
—	(3.25)	80	27	7.31	12	12	—	12	—	11.5	—	11.5	—	11	—	11.5	—	11	—	11.5	—	11	—	11
—	3.5	80	27	7.88	12	13	—	13	—	12.5	—	12.5	—	12	—	12.5	—	12	—	12.5	—	12.5	—	12.5
—	(3.75)	80	27	8.44	12	14	—	13.5	—	13	—	13	—	12.5	—	13.5	—	13	—	13.5	—	13.5	—	13.5
4	—	90	27	9.00	12	15	—	14.5	—	14	—	14.5	—	14	—	15	—	14.5	—	15	—	14.5	—	15
—	4.5	90	27	10.13	12	16.5	—	16	—	15	—	15.5	—	15	—	16	—	15.5	—	16	—	15.5	—	16
5	—	100	27	11.25	12	18	—	17.5	—	17	—	16.5	—	16	—	17.5	—	17	—	18	—	17.5	—	18
—	5.5	100	27	12.38	12	20	—	19	—	18.5	—	18	—	17.5	—	19	—	18	—	19.5	—	19	—	19.5
6	—	110	32	13.50	10	21.5	—	21	—	20	—	19.5	—	19	—	20	—	19.5	—	20	—	19.5	—	20
—	(6.5)	110	32	14.63	10	23	—	22.5	—	21.5	—	21	—	20	—	21	—	20	—	21	—	20	—	21
—	7	110	32	15.75	10	25	—	24	—	23	—	22	—	21.5	—	22	—	21.5	—	22	—	21.5	—	22
8	—	125	32	18.00	10	28	—	27	—	26	—	25	—	24.5	—	25	—	24.5	—	25	—	24.5	—	25
—	9	125	32	20.25	10	32	—	30	—	29	—	28	—	27	—	28	—	27	—	28	—	27	—	28
—	10	140	40	22.50	10	35	—	33	—	32	—	31	—	30	—	31	—	30	—	31	—	30	—	31
—	—	140	40	24.75	10	38	—	36	—	35	—	34	—	33	—	34	—	33	—	34	—	33	—	34
—	11	160	40	27.00	10	42	—	39	—	38	—	37	—	36	—	37	—	36	—	37	—	36	—	37
—	12	160	40	31.50	10	48	—	45	—	44	—	43	—	42	—	43	—	42	—	43	—	42	—	43
—	14	180	50	36.00	10	55	—	52	—	51	—	50	—	49	—	49	—	48	—	49	—	48	—	49
—	—	180	50	36.00	10	55	—	52	—	51	—	50	—	49	—	48	—	47	—	48	—	47	—	48

*Indicates the working depth of profile.
†Gives the recommended number of teeth.