

IS : 5731 - 1970
(Reaffirmed 1994)

AMENDMENT NO. 2 MARCH 2000
TO
IS 5731 : 1970 SPECIFICATION FOR ANTIMONY
SULPHIDE FOR EXPLOSIVE AND PYROTECHNIC
COMPOSITIONS

(Page 4, clause 2.2) — Insert the following after 2.2:

'2.3 For Defence Purpose

2.3.1 Performance Test — The material shall also pass the performance test if required by Defence Authorities, in accordance with the method prescribed by them.'

[Page 4, Table 1, Sl No. (ii), col 2] — Substitute 'pH for Acidity'.

[Page 4, Table 1, Sl No. (ii), col 2] — Substitute '5 5 to 7 5' for 'to pass the test'.

(Page 6, clause A-3) — Substitute the following for the existing:

'A-3 METHODS FOR DETERMINATION OF pH

A-3.1 Apparatus

A-3.1.1 Electronic pH Meter - Any standard pH meter calibrated against standard buffer solution at two pH values (pH 4 and pH 9)

A-3.2 Reagents

A-3.2.1 Standard Buffer Solution — The standard solutions one of pH 4 and the other of pH 9.

A-3.2.2 Distilled Water - (pH 6.2 to 7.2).

A-3.3 Procedure

A-3.3.1 Take 5 g of material passing through 150 microns IS sieve with 100 ml of freshly boiled and cooled distilled water. Filter and wash the residue thoroughly with 25 ml distilled water. Determine the pH of the aqueous extract with the pH meter. Make atleast two determinations on test samples from two separate portions and if the value differs by more than 0.4, repeat with two fresh portions. Reject the highest and lowest and report the average.

A-3.3.2 Excessive contact of this solution with air shall be avoided.'

(CHD 26)

Reprography Unit, BIS, New Delhi, India