

AMENDMENT NO. 1 MAY 1993
TO
IS 8173 : 1984 PROPELLER SHAFTS WITH KEYWAY OF
DIAMETER 20 TO 160 mm
(First Revision)

(Page 4, clause 3.1, line 1) — Substitute 'IS 305 : 1981 Aluminium bronze, ingots and castings (*second revision*)' for 'IS 305 : 1961*'.

(Page 4, clause 4.3.2) — Substitute the following clause for the existing:

'4.3.3 For 80 mm diameter and above, the key shall be secured by atleast two securing slotted cheese head screws in accordance with IS 1366 : 1982 Slotted cheese head screws (*second revision*).'

(Page 4, clause 4.4, line 3) — Substitute the following Indian Standards for IS 4218 : 1967§ :

IS 4218 (Part 1) : 1976 ISO metric screw threads : Part 1 Basic and design profiles (*first revision*)

IS 4218 (Part 2) : 1976 ISO metric screw threads : Part 2 Diameter pitch combinations (*first revision*)

IS 4218 (Part 3) : 1976 ISO metric screw threads : Part 3 Basic dimensions for design profiles (*first revision*)

IS 4218 (Part 4) : 1976 ISO metric screw threads : Part 4 Tolerancing system (*first revision*)

IS 4218 (Part 5) : 1979 ISO metric screw threads : Part 5 Tolerances (*first revision*)

IS 4218 (Part 6) : 1978 ISO metric screw threads : Part 6 Limits of sizes for commercial bolts and nuts (diameter range 1 to 52 mm) (*first revision*)

(TED 19)

Reprography Unit, BIS, New Delhi, India