

AMENDMENT NO. 1 NOVEMBER 1985

TO

IS:8336-1977 SPECIFICATION FOR THERMOELECTRIC
PYRANOMETER

(Page 2, clause 0.2) - Substitute the following for the existing clause:

'0.2 Measurements of the total amount of energy received from the sun and sky are of fundamental importance in meteorology and in studies of the exchange and transformation of energy in the earth-atmosphere system and in biology, medicine, agriculture, architecture and industry. The solar radiation which reaches the earth's surface is contained in the range of wavelengths 300 to 400 nm. The quantity of radiation is expressed as the amount of radiant energy falling on unit area of the surface in unit time and is expressed in W m^{-2} .

The solar constant, the mean value of the quantity of solar radiation reaching a surface placed normal to the rays of the sun just outside the earth's atmosphere at mean sun-earth distance is assured to be about

$$1\,367 \pm 7 \text{ W m}^{-2} \text{ .}$$

(Page 2, clause 0.3, line 6) - Delete the word 'total'.

(Page 5, Fig. 2) - Substitute 'R 25' for 'R 35' and 'R 15' for 'R 25'.

(Page 7, Table 1, under 'Dimensions') - Substitute '50' for '70', '30' for '50' and '55' for '75'.

(Page 7, clause 5.1.5, line 3) - Substitute ' $\pm \text{W m}^{-2}$ ' for ' $\pm 0.3 \text{ m W/cm}^2$ ' and '11 to $\mu\text{V/W m}^{-2}$ ' for '8 mV/cal/cm²/min'.

(Page 8, clause 5.1.14) - Add the following sentence at the end:

'The mounting plate can also be made out of anodised (white) aluminium.'

(Page 8, clause 5.2.3, line 2) - Substitute '30 mm/h or 60 mm/h' for '25 mm/h'.

(Page 8, clause 5.3.2) - Substitute the following for the existing clause:

'5.3.2 It shall have a minimum length of 30 m and a minimum width of 110 mm in the graduated portion. The overall width of the roll chart shall not be less than 130 mm, charts with 250 mm graduated portion are also acceptable.'

(Page 10, clause 5.3.3, line 4) - Substitute '30 mm/h' for '25 mm/h'.

[Page 11, clause 7.1.2(b)] - Substitute ' $\mu\text{V}/\text{W}_r^{-2}$ ' for ' $\text{mV}/\text{cal}/\text{cm}^2/\text{min}$ '.

(EDC 69)