

**AMENDMENT NO. 1 APRIL 2002
TO
IS 3986 : 1988 SPECIFICATION FOR SODIUM LAURYL
SULPHATE FOR COSMETIC INDUSTRY**

(Third Revision)

[Page 2, Table 1, Sl No. (viii)] — Substitute the following for the existing:

(2)	(3)	(4)	(5)
'pH (1 percent solution)	7.5-10.5	7.5-10.5	7.5-11.0'

(Page 6, clause A-7) — Substitute the following for the existing:

A-7 DETERMINATION OF SODIUM SULPHATE

A-7.1 Reagents

A-7.1.1 Dithiozone Solution — 0.05% m/v in acetone.

A-7.1.2 Nitric acid — 1M.

A-7.1.3 Acetone

A-7.1.4 Lead Nitrate — 0.01M : 3.312 g diluted to 1000 ml with water.

A-7.1.5 Dichloroacetic Acid Solution — Dilute 67 ml of dichloroacetic acid to 300 ml with water and neutralize to litmus paper using 10M ammonia. Cool, add 33 ml of Dichloroacetic acid and dilute with water to 600 ml.

A-7.2 Procedure

Dissolve 0.5 g of the material in 20 ml of water, warming gently if necessary and add 1 ml of 0.05% m/v solution of dithiozone in acetone. If the solution is red, add 1M Nitric acid, dropwise, until it becomes bluish green. Add 2 ml of dichloroacetic acid solution and 80 ml of acetone and titrate with 0.01M lead nitrate until permanent orange-red colour is obtained.

Amend No. 1 to IS 3986 : 1988

A-7.3 Calculation

$$\text{Sodium Sulphate(\%)} = \frac{V \times N \times 0.00142 \times 100}{0.01 \times M}$$

where

V = ml of lead nitrate required,

N = molarity of lead nitrate solution, and

M = mass of sample taken for test.

(PCD 19)