

**IS:4084-1978 SPECIFICATION FOR
EYELETS AND WASHERS (SAIL)**

(First Revision)

AMENDMENT NO. 1 AUGUST 1979

Corrigendum

*(Page 1, Committee Composition, Members, line 12) -
Substitute 'SHRI B.K. MEHAN' for 'SHRI B.K. MOHAN'.*

AMENDMENT NO. 2 AUGUST 1981

Alteration

*(Pages 6, 7 and 8, Tables 1, 2 and 3, second
column heading) - Substitute 'STARTING THICKNESS OF
METAL' for 'THICKNESS OF METAL AT LIP, Min '*

Addendum

*(Page 4, clause 3.2) - Add the following new
clauses after 3.2:*

'3.3 The starting thickness of sheet or strip shall be as given in Tables 1, 2 and 3. A deviation of ± 0.02 mm shall be allowed for brass sheet or strip. Deviation in aluminium sheet or strip shall be as given in Table 6 of IS:2676-1964.

3.4 Maximum reduction due to forming shall not exceed 0.05 mm when measured anywhere on the periphery of the lip of the eyelets.

3.5 A deviation of ± 0.1 mm shall be allowed on all dimensions wherever deviation is not mentioned.'

(CPDC 22)

Reprography Unit, ISI, New Delhi, India