

**IS:4084-1978 SPECIFICATION FOR
EYELETS AND WASHERS (SAIL)**

(First Revision)

AMENDMENT NO. 1 AUGUST 1979

Corrigendum

*(Page 1, Committee Composition, Members, line 12) -
Substitute 'SHRI B.K. MEHAN' for 'SHRI B.K. MOHAN'.*

AMENDMENT NO. 2 AUGUST 1981

Alteration

*(Pages 6, 7 and 8, Tables 1, 2 and 3, second
column heading) - Substitute 'STARTING THICKNESS OF
METAL' for 'THICKNESS OF METAL AT LIP, Min '*

Addendum

*(Page 4, clause 3.2) - Add the following new
clauses after 3.2:*

**'3.3 The starting thickness of sheet or strip shall
be as given in Tables 1, 2 and 3. A deviation of
+0.02 mm shall be allowed for brass sheet or strip.
Deviation in aluminium sheet or strip shall be as
given in Table 6 of IS:2676-1964.**

**3.4 Maximum reduction due to forming shall not exceed
0.05 mm when measured anywhere on the periphery of the
lip of the eyelets.**

**3.5 A deviation of +0.1 mm shall be allowed on all
dimensions wherever deviation is not mentioned.'**

(CPDC 22)

Reprography Unit, ISI, New Delhi, India