

AMENDMENT NO. 1 APRIL 1978
TO
IS : 3348 - 1965 SPECIFICATION FOR
FIBRE INSULATION BOARDS

Alterations

(*Pages 6 and 7, clause 4.5*) — Substitute the following for the existing clause:

'4.5 Sound Absorption — The sound absorption coefficient when determined by the standing wave method shall be as follows:

<i>Frequency</i>	<i>Absorption Coefficient</i>
<i>c/s</i>	<i>Min</i>
125	0.1
250	0.1
500	0.2
1 000	0.3
2 000	0.5

4.5.1 The sound absorption coefficient may be determined by reverberation chamber method, the criteria of acceptance in which case shall be agreed upon, between the purchaser and the supplier.'

(*Page 6, foot-note with '*' mark*) — Delete.

(*Page 7, foot-note with '*' mark*) — Delete.

(*Page 8, foot-note with '*' mark*) — Delete the words '(under preparation)'.

(*Page 10, clause 9.5*) — Substitute the following for the existing clause:

'9.5 Test for Sound Absorption — The same test pieces, 30 × 30 cm, for thermal conductivity may be used for sound absorption before performing the former test. The test shall be done as mentioned under 4.5.'

(*Page 16, clause E-2.2, line 1*) — Substitute '15 mm' for '2.2 mm'.

(BDC 20)