

**AMENDMENT NO. 2 AUGUST 2007
TO
IS 3521 : 1999 INDUSTRIAL SAFETY BELTS AND
HARNESSES — SPECIFICATION**

(Third Revision)

(Page 2, clause 5.1, para 1) — Substitute the following for the existing text:

The minimum width of all straps shall be 40 mm except shoulder retaining strap, which shall be of minimum width of 20 mm.'

(Page 8, Table 2, clause reference) — Substitute 'Clause B-2.1' for 'clauses B-2.1 and D-4'

(Page 9, Annex D) — Delete the subtitle 'Dynamic Testing Drop Distances and Attachment Points for Fall Arresting Harness (Class A)'.

(Page 10, clause D-4) — Substitute the following for the existing text:

Fit the articulated human dummy with the harness equipped with lanyard and without an energy absorber.

Suspend the dummy by its upper attachment point and raise to an extent that the total free fall shall be of 4 m and the maximum horizontal distance from the central line shall be 300 mm. Hold it with the quick release device.

Release the dummy without initial velocity, the feet first free fall being 4 m. Observe whether the harness releases the dummy. Also observe the orientation of the dummy and measure angle between the longitudinal axis of the dorsal plane of the dummy and the vertical.

Using same rope, repeat the test procedure within 15 ± 1 min suspended from its lower attachment point and achieve a head first free-fall of 4 m.'