

**AMENDMENT NO. 2      APRIL 1990**  
**TO**  
**IS : 3523 - 1974 SPECIFICATION FOR METAL TRAVELLERS FOR**  
**RING SPINNING FRAME**  
*( Second Revision )*

[ Page 2, Table 1 ( see also Amendment No. 1 ) ] — Substitute the following for the existing table:

**TABLE 1 WEIGHT OF TRAVELLERS**

( Clause 3.1 )

| TRAVELLER<br>NUMBER | WEIGHT OF<br>1 000 TRAVELLERS<br>IN g | WEIGHT OF 1 000<br>TRAVELLERS BASED ON<br>R-20 SERIES OF<br>PREFERRED NUMBER<br>IN g | TRAVELLER<br>NUMBER | WEIGHT OF<br>1 000 TRAVELLERS<br>IN g | WEIGHT OF 1 000<br>TRAVELLERS BASED ON<br>R-20 SERIES OF<br>PREFERRED NUMBER<br>IN g |
|---------------------|---------------------------------------|--------------------------------------------------------------------------------------|---------------------|---------------------------------------|--------------------------------------------------------------------------------------|
| (1)                 | (2)                                   | (3)                                                                                  | (1)                 | (2)                                   | (3)                                                                                  |
| 30/0                | 4.5                                   | 4.0                                                                                  | 1                   | 58.0                                  | 56.0                                                                                 |
| 30/0                | —                                     | 4.5                                                                                  | 1                   | —                                     | 63.0                                                                                 |
| 29/0                | 5.2                                   | 5.0                                                                                  | 2                   | 68.0                                  | 71.0                                                                                 |
| 28/0                | 5.8                                   | 5.6                                                                                  | 3                   | 78.0                                  | 80.0                                                                                 |
| 27/0                | 6.5                                   | 6.3                                                                                  | 4                   | 84.0                                  | 80.0                                                                                 |
| 26/0                | 7.1                                   | 7.1                                                                                  | 5                   | 94.0                                  | 90.0                                                                                 |
| 25/0                | 7.8                                   | 8.0                                                                                  | 6                   | 104.0                                 | 110.0                                                                                |
| 24/0                | 8.4                                   | 8.0                                                                                  | 7                   | 113.0                                 | 110.0                                                                                |
| 23/0                | 9.1                                   | 9.0                                                                                  | 8                   | 130.0                                 | 125.0                                                                                |
| 22/0                | 9.7                                   | 10.0                                                                                 | 9                   | 149.0                                 | 140.0                                                                                |
| 21/0                | 10.4                                  | 10.0                                                                                 | 10                  | 169.0                                 | 160.0                                                                                |
| 20/0                | 11.0                                  | 11.0                                                                                 | 10                  | —                                     | 180.0                                                                                |
| 19/0                | 11.7                                  | —                                                                                    | 11                  | 194.0                                 | 200.0                                                                                |
| 18/0                | 12.3                                  | 12.5                                                                                 | 12                  | 207.0                                 | 200.0                                                                                |
| 17/0                | 13.0                                  | 12.5                                                                                 | 13                  | 220.0                                 | 225.0                                                                                |
| 16/0                | 13.6                                  | 14.0                                                                                 | 14                  | 240.0                                 | 250.0                                                                                |
| 15/0                | 14.3                                  | 14.0                                                                                 | 15                  | 259.0                                 | 250.0                                                                                |
| 14/0                | 15.6                                  | 16.0                                                                                 | 16                  | 272.0                                 | 280.0                                                                                |
| 13/0                | 16.8                                  | 16.0                                                                                 | 17                  | 285.0                                 | 280.0                                                                                |
| 12/0                | 18.1                                  | 18.0                                                                                 | 18                  | 298.0                                 | 315.0                                                                                |
| 11/0                | 19.4                                  | 20.0                                                                                 | 19                  | 311.0                                 | 315.0                                                                                |
| 10/0                | 21.0                                  | 20.0                                                                                 | 20                  | 324.0                                 | 315.0                                                                                |
| 9/0                 | 23.0                                  | 22.5                                                                                 | 21                  | 341.0                                 | 355.0                                                                                |
| 8/0                 | 24.0                                  | 25.0                                                                                 | 22                  | 356.0                                 | 355.0                                                                                |
| 7/0                 | 28.0                                  | 28.0                                                                                 | 23                  | 378.0                                 | 355.0                                                                                |
| 6/0                 | 31.0                                  | 31.5                                                                                 | 24                  | 389.0                                 | 400.0                                                                                |
| 5/0                 | 33.0                                  | 31.5                                                                                 | 25                  | 405.0                                 | 400.0                                                                                |
| 4/0                 | 36.0                                  | 35.5                                                                                 | 26                  | 421.0                                 | 400.0                                                                                |
| 3/0                 | 41.0                                  | 40.0                                                                                 | 27                  | 437.0                                 | 450.0                                                                                |
| 2/0                 | 45.0                                  | 45.0                                                                                 | 28                  | 454.0                                 | 450.0                                                                                |
| 1/0                 | 52.0                                  | 50.0                                                                                 | 29                  | 470.0                                 | 450.0                                                                                |
|                     |                                       |                                                                                      | 30                  | 486.0                                 | 500.0-800.0                                                                          |

NOTE 1 — Tolerance on weight shall be  $\pm 3$  percent.

NOTE 2 — In case the weight of 1 000 travellers is different from those specified in col 2, the tolerance of  $\pm 3$  percent shall be applicable on the declared weight by the manufacturer.

NOTE 3 — Weight of a given traveller number shall be the same irrespective of its shape, section and dimensions.

NOTE 4 — The weights based on R-20 series given in col 3 are adopted internationally and should be preferred.