


AMENDMENT NO. 1 JULY 1985
TO
IS : 7513 - 1974 GRAPHICAL SYMBOLS FOR FLUID POWER
SYSTEMS

(Page 2, clause 2.1.2.5, under column ' Application ') — Substitute ' semi-rotary actuator/oscillator' for ' oscillator '.

(Page 7, clause 3.7, under column ' Symbol ') — Delete the symbol for ' hydraulic to pneumatic '.

(Page 9, clause 4.2.2.7, under column ' Symbol ') — Substitute the following for the existing figure:



DETAILED




SIMPLIFIED

(Page 10, 4.2.3.5, under column ' Symbol ') — Substitute the following for the existing figure:



(Page 12, clause 4.4.7, under column ' Symbol ') — Substitute the following for the existing figure:




(Page 15, clause 5.3.1.4) — Delete along with all the entries against it.

(Page 19, clause 6.2.4.1.c, under column ' Description ') — Substitute ' by different control areas ' for ' by differential pressure '.

(Page 19, clause 6.2.4.1.c, under column ' Use of the Equipment or Explanation of the Symbol ') — Insert the following matter in this column:

' In the symbol the larger rectangle represents the larger control area, that is the priority phase. '

(Page 19, clause 6.2.4.1.c, under column ' Symbol ') — Substitute the following for the existing figure:



(*Page 21, clause 7.1.2.1, under column ' Symbol '*) — Substitute the following for the existing figure:



(*Page 22, clause 8, third line*) — Add the following at the end:

' if clearly stated '

(*Page 23, clause 8.3.2*) — Add the following new matter after this clause:

' EXPLANATORY NOTE

In the preparation of this standard considerable assistance has been derived from ISO 1219-1976 Fluid power systems and components — Graphic symbols, issued by International Organization for Standardization (ISO) '.