

**AMENDMENT NO. 2 NOVEMBER 1993
TO
IS 7809 (Part 1) : 1975 SPECIFICATION FOR
PRESSURE SENSITIVE ADHESIVE TAPES FOR
ELECTRICAL PURPOSES**

PART 1 GENERAL REQUIREMENTS

(Page 5, clause 6.1) — Replace existing clause by the following:

'6.1 Cora Diameter — The preferred internal diameters of the cores on which tapes are rolled shall be 25 mm to 50 mm or greater, and as agreed to between the purchaser and supplier.'

(Page 7, clause 6.3) — Replace existing clause by the following:

'6.3 The length of tape on a roll shall be a multiple of 5 m and as agreed to between the purchaser and the supplier. The actual length shall not be less than the stated length.'

(Page 7, clause 7.1) — Replace existing clause by the following:

'7.1 After the roll of tape has been stored flat on the cut edges in the original sealed packing at a temperature between 10 and 40°C and a relative humidity of 45 to 75 percent for a period of twelve months from the date of manufacture, it shall be tested and shall comply with the requirements as prescribed in this standard.'

(Page 7, clause 9.1) — Replace existing clause by the following:

'9.1 Each label of an insulating tape or its wrapper, or a package containing unit or a number of unit rolls of tape or the central paper core on which the tape is wrapped shall have the following information clearly and indelibly marked on it:

- a) Designation of the tape, in accordance with 3;
- b) Appearance of the tape according to 4, for example, transparent, uncoloured, opaque-blue etc;
- c) The nominal width of the tape;
- d) The nominal length of the tape on each roll;
- e) The nominal thickness of the tape;
- f) Manufacturer's or supplier's identification mark and batch number,