

AMENDMENT NO. 1 SEPTEMBER 1978
TO
IS : 7827 (Part II)-1975 SPECIFICATION FOR
ELECTRICAL WIND SCREEN WIPERS

PART II WIPER MOTORS

Alterations

[*Page 6, clause 4.1.3*] — Substitute the following for the existing clause:

'4.1.3 Acceptance Tests — Visual examination (*see 4.2*), no-load test (*see 4.3*), parking test (*see 4.6*), continuous torque test (*see 4.8*) and high voltage (flash) test (*see 4.17*) shall be acceptance tests.'

(*Page 7, clause 4.6.1, last line*) — Substitute ' off ' for ' park '.

(*Page 7, clause 4.8.1*) — Substitute the following for the existing clause:

'4.8.1 With an applied voltage of 6.75 ± 0.1 , 13.5 ± 0.25 and 27 ± 0.5 V for 6, 12 and 24 V wiper motors respectively maintained at the motor terminals, the unit shall be allowed to run for a period of 30 minutes against a constant torque equal to that declared by the manufacturer as the continuous torque rating of the unit. At the end of the 30-minute period the current consumption of the motor shall not exceed and the speed shall not be less than values specified by the manufacturer as continuous rating of the unit. '

(*Page 8, clause 4.14.5, line 2*) — Substitute ' water at the rate of not less than 10 ml/s, covering ' for ' water, covering '.

Addenda

[*Page 5, clause 4.1.1 (r)*] — Add the following new matter after **4.1.1 (r)**:

' s) High voltage (flash) test (*see 4.17*). '

[*Page 6, clause 4.1.4(e)*] — Add the following new matter after **4.1.4(e)**:

' f) High voltage (flash) test (*see 4.17*). '

(*Page 9, clause 4.14.8*) — Add the following new clause after **4.14.8**:

' **4.14.9** The motor shall be subjected to high voltage (flash) test (see **4.17**) after this test. The test piece shall satisfactorily withstand this test without arcing or puncture. '

(Page 9, clause **4.16**) — Add the following new clause after **4.16**:

' **4.17 High Voltage (Flash) Test** — The motor shall be isolated from the internal ground and then shall be subjected to a flash test for a period of not more than 5 seconds, with an alternating current of 500 V rms at any convenient frequency between 40 and 60 Hz between any of the terminals and the ground. The motor shall satisfactorily withstand this test without arcing or puncture. '

(ETDC 14)