

AMENDMENT NO. 1 JANUARY 2022

TO

IS 7872 : 2020 DEEP FREEZERS — SPECIFICATION

(*Second Revision*)

(*Foreword, para 3*) — Insert the following at the end:

‘The major changes in this revision are as follows:

- a) The scope has been expanded to cover both hardtop and glass top type freezers;
- b) New terminologies have been added;
- c) The compliance requirement for the compressor has been added;
- d) Energy consumption test has been included;
- e) Provision for the location of test package and M-package has been included;
- f) Maximum storage limit line has been defined;
- g) Climate class N and ST has been added;
- h) Safety test as per IS/IEC 60335-2-89 has been incorporated in place of IS 302-2-24, including safety test for flammable refrigerants;
- j) Temperature sensor location has been modified; and
- k) Method of volume measurement has been modified.’

(*Page 4, clause 5.4.1, second sentence*) — Substitute the following for existing:

‘Compliance is checked by carrying out any one of the tests specified in 5.4.2 to 5.4.4.’

(*Page 5, clause 6.2, line 4*) — Substitute the word ‘on’ for ‘of’.

(Page 5, clause 7, para 1) — Substitute the following for existing:

‘The refrigerating system shall not have sound pressure level more than 65 dBA for commercial places under the normal running operation at no load at prevailing room temperature and should not transmit vibration to adjoining portions of the surroundings.

NOTE — For any deviation between the limit specified in this standard and the sound pressure level specified in the *Noise Pollution (Regulation and Control) Rules*, 2000 issued by the Ministry of Environment, Forest and Climate Change, the limits specified in *Noise Pollution Rules* shall prevail.’

(Page 6, clause 8.3, para 1, last line) — Insert the following at the end:

‘as given below: ’

(Page 8, clause 11.2, para 2, last line) — Delete the word ‘below’.

(Page 9, clause 11.3) — Insert the following at the end:

‘At the end of the test, time for the temperature rise shall not be less than 10 percent of the value declared by the manufacturer.’

(Page 9, clause 11.5, para 2, first sentence) —Substitute the following for existing:

‘Deflection shall not be more than 1.04 cm per m when loaded with 195.3 kg/m².’