



AMENDMENT NO. 1 DECEMBER 1985

TO

IS : 7953-1976 SPECIFICATION FOR HORN RINGS FOR
AUTOMOBILES

(Page 6, clause 6.5) - Substitute the following
for the existing clause:

'6.5 Endurance Test - The horn ring shall be suitably mounted and operated at two diametrically opposite points of the ring, alternately, for 100 000 cycles without failure, with an inductive load of 120 percent of the rated current through the horn switch contacts. Each cycle shall consist of sequencing through each position with travel time and dwell time as given below. The resistance in the system shall be 0.05 ohm for rated voltage of 6 V, 0.10 ohm for rated voltage of 12 V and 0.20 ohm for rated voltage of 24 V, the resistance at terminals and contacts being included.

Travel time (time from one 0.1 to 0.5 seconds
position to the other

Dwell time (time in each 0.1 to 2.0 seconds,
position)

NOTE - The travel and dwell periods are for guidance only. The actual value which depend upon the application shall be subject to agreement between the manufacturer and the user.

6.5.1 The horn ring after being subjected to this test shall be allowed to come down to room temperature and subjected to voltage drop test (see 6.9). The voltage drop at rated current (with normal force of 20 N applied to the ring at any point) shall not exceed 200 mV.

(EIDC 14)

Reprography Unit, ISI, New Delhi, India