

AMENDMENT NO. 2 SEPTEMBER 2026
TO
IS 11928 : 2023 TEXTILES — ROUNDSLINGS MADE OF MAN-MADE FIBRES
FOR GENERAL SERVICE — SPECIFICATION
(First Revision)

[Page 3, clause 4.2.5, (see also Amendment No. 1)] — Substitute the following for the existing:

‘4.2.5 Colour Coding

Roundslings shall have a protective outer cover of a colour which identifies their working load limit (WLL) according to the following code:

NOTE — Working load limit is equal to the safe working load in straight pull of the sling in basic configuration.

<i>Sl No.</i>	<i>WLL</i>	<i>Colour</i>
(1)	(2)	(3)
i)	1	Violet
ii)	2	Green
iii)	3	Yellow
iv)	4	Grey
v)	5	Red
vi)	6	Brown
vii)	8	Blue
viii)	12	Orange
ix)	Above 12	Orange

(Page 10, Annex C, Table 1) — Substitute the following for the existing:

‘Table 1 Safe Working Loads and Strength Corresponding to Working Load Limits

(Clause C-1)

Sl No.	Working Load Limit for Each Sling in Basic Configuration	Corresponding Minimum Strength of the Roundsling	Safe Working Loads,					
			<i>Max</i>					
			Straight Lift M ¹⁾ = 1.0	Choked Lift M = 0.8	Basket Hitch		2 Legged Max 90° M = 1.4	4- Legged Sling, Max, 90° M = 2.0
	t	kN	t ²⁾	t	t	t	t	t
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	1.0	58.8	1.0	0.8	2.0	1.4	1.4	2.0
ii)	2.0	117.7	2.0	1.6	4.0	2.8	2.8	4.0
iii)	3.0	176.5	3.0	2.4	6.0	4.2	4.2	6.0
iv)	4.0	235.4	4.0	3.2	8.0	5.6	5.6	8.0
v)	5.0	294.2	5.0	4.0	10.0	7.0	7.0	10.0

Price Group 1

Amendment No. 2 to IS 11928 : 2023

Table 1 (Concluded)

Sl No.	Working Load Limit for Each Sling in Basic Configuration	Corresponding Minimum Strength of the Roundsling	Safe Working Loads,					
			<i>Max</i>					
			Straight Lift $M^{(1)} = 1.0$	Choked Lift $M = 0.8$	Basket Hitch		2 Legged <i>Max</i> 90° $M = 1.4$	4- Legged Sling, <i>Max</i> , 90° $M = 2.0$
	t	kN	t ⁽²⁾	t	t	t	t	t
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
vi)	6.0	353.0	6.0	4.8	12.0	8.4	8.4	12.0
vii)	8.0	470.7	8.0	6.4	16.0	11.2	11.2	16.0
viii)	12.0	706.1	12.0	9.6	24.0	16.8	16.8	24.0
ix)	Above 12.0	—	—	—	—	—	—	—
NOTES 1 For slings with working load limit in basic configuration of above 12 tons, the corresponding minimum breaking strength of the roundslings shall be evaluated by multiplying the declared working load limit with safety factor as specified in 4.8. 2 For slings with working load limit in basic configuration of above 12 tons, the maximum safe working load shall be evaluated by multiplying the declared working load limit with the mode factor, as given in Fig. 3, for the specified mode of assembly.								

$M^{(1)}$ = Mode factor

t⁽²⁾ = ton = 1 000 kg

1 kN = 102 kgf approximately