

**AMENDMENT NO. 1 JUNE 2017
TO
IS 12009 : 1995 AUTOMOTIVE VEHICLE — SAFETY
REQUIREMENTS FOR SIDE DOOR OF PASSENGER
CARS — RECOMMENDATIONS**

(First Revision)

(First cover page) — Substitute the following title for the existing title:

‘भारतीय मानक
स्वचलन वाहन – यात्री गाड़ियों एवं एल 7-एम श्रेणी के
क्वाट्रीसाइकल वाहनों के लिये साइडडोर की सुरक्षा अपेक्षाओं की
सिफारिशें
(पहला पुनरीक्षण)

Indian Standard
AUTOMOTIVE VEHICLE — SAFETY REQUIREMENTS FOR
SIDE DOOR OF PASSENGER CARS AND QUADRICYCLES
OF CATEGORY L7-M — RECOMMENDATIONS
(*First Revision*)’

(Page 1, Title) — Substitute the following title for the existing title:

‘*Indian Standard*
AUTOMOTIVE VEHICLE — SAFETY REQUIREMENTS FOR
SIDE DOOR OF PASSENGER CARS AND QUADRICYCLES
OF CATEGORY L7-M — RECOMMENDATIONS
(*First Revision*)’

(Page 1, clause 1) — Substitute the following for the existing clause:

Amendment No. 1 to IS 12009 : 1995

‘1 SCOPE

This standard specifies the strength requirements for side doors of passenger cars and quadricycles of category L7-M to minimize the safety hazards caused by intrusion into the passenger compartment in a side impact accident.’

(Page 1, *clauses 3, 3.1, 3.1.1, 3.1.2 and 3.1.3*) — Substitute the following for the existing clauses:

‘3 REQUIREMENTS

The passenger car and quadricycles of category L7-M shall be able to meet the requirements given in **3.1** when any of its side doors is tested according to the procedure given in Annex A.’

3.1 With seats installed in the vehicle, and located in any horizontal, inclined or vertical position to which they may be adjusted and at any seat back angle to which they may be adjusted, the car and quadricycles of category L7-M shall meet the requirements of **3.1.1** to **3.1.3**.’

3.1.1 The average initial crush resistance shall not be less than:

- a) 0.6 times the kerb weight of the car or 10 kN, whichever is less.
- b) 0.42 times the kerb weight of the quadricycles of category L7-M or 7 kN, whichever is less.

3.1.2 The average intermediate crush resistance shall not be less than:

- a) 1.2 times the kerb weight of the car or 20 kN, whichever is less.
- b) 0.84 times the kerb weight of the quadricycles of category L7-M or 14 kN, whichever is less.

3.1.3 The peak crush resistance shall not be less than:

- a) 2 times the kerb weight of the car or 55 kN, whichever is less.
- b) 1.4 times the kerb weight of the quadricycles of category L7-M or 38.5 kN, whichever is less.’

(TED 29)

Publication Unit, BIS, New Delhi, India