

**AMENDMENT NO. 1 OCTOBER 2008
TO
IS 12025 : 1987 RECOMMENDATIONS FOR MEASUREMENT OF QUALITY
CHARACTERISTICS FOR PISTONS**

(Page 1, clause 3.1) — Substitute the following for the existing:

‘3.1 Soak the piston at $20 \pm 1^{\circ}\text{C}$ until it reaches the temperature.’

(Page 2, clause 3.2.2, second sentence) — Substitute the following for the existing:

‘A mechanical comparator with least count of 0.01 mm/Precision Measuring microscope/Shadow graph or suitable Instrument shall be used.’

(Page 2, clause 3.4.2) — Add the following new clause after 3.4.2:

‘3.4.3 Precision Measuring Microscope/Shadow graph/Height masters may be used for Groove axial width measurement.’

(Page 4, clause 3.5.2) — Add the following new clause after 3.5.2:

‘3.5.3 Ovality may also be checked with form testing machines.’

(Page 4, clause 3.6.2) — Add the following new clause after 3.6.2:

‘3.6.3 Compression height may also be measured with Height master/3D-co-ordinate machines.’

(Page 4, clause 3.7.2) — Add the following new clause after 3.7.2:

‘3.7.3 Top land height may also be measured with Height master/3D-co-ordinate machines.’

(Page 10, clause 5.1, Measuring procedure) — Add the following at the end:

‘or by Height master/3D co-ordinate machines.’

Amend No. 1 to IS 12025 : 1987

(Page 13, clause 5.5, Measuring procedure, first sentence) — Add the following at the end:

‘or form testing machine can be used for measurement.’