

AMENDMENT NO. 1 OCTOBER 1996
TO
IS 12109 : 1987 GENERAL REQUIREMENTS FOR
LIGHT DUTY SEWING MACHINE HEADS FOR
INDUSTRIAL USE

(Page 3, Table 2) — Substitute the following for the existing:

TABLE 2 SEWING REQUIREMENTS
(Clause 8)

SI No.	Itam	Needle	Type of Thread!	Fabric	No. of Layers	Stiteh Langth (Approx) mm	Sewing Speed (Approx) rev/mi	Sewing Length (Approx) mm
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	Regular sawing	14	Cotton thread	Shirting cloth	2	1.5 & 3	1 000 & 1 800	1 000
ii)	Stem sewing	14	Cotton	Muslin (length of step approx 25 mm)	4 to 12 and 12 to 4	do	1 000	300
iii)	Heavy materiel	16	Cotton thread	Drill cloth	2	3	1 000	1 000
iv)	Light material	11	Silk thread	Rain synthetic fabric	2	1.5	1 800	1 000
v)	Sewing test for straight-ness	14	—	Blue print paper	2	3	1 500	300 with hands free. The Max height of arc shall be below 5 for the free chord of 200

(LM 18)