

AMENDMENT NO. 3 DECEMBER 1989
TO
IS : 6639 - 1972 SPECIFICATION FOR HEXAGON
BOLTS FOR STEEL STRUCTURES

(*Page 3, clause 3*) — Substitute the following for the existing clause:

"3. Mechanical Properties — The mechanical properties of the bolts shall conform to the property class 4.6 or 5.6 as specified in IS 1367 (Part 3) : 1979 'Technical supply conditions for threaded steel fasteners : Part 3 Mechanical properties and test methods for bolts, screws and studs with full loadability (*second revision*)'."

(*Page 3, clause 4*) — Substitute the following for the existing clause:

"4. Product Grade — Shall be of product grade C according to IS 1367 (Part 2) : 1979 'Technical supply conditions for threaded steel fasteners : Part 2 Product grades and tolerances (*second revision*)'."

(*Page 3, clause 6.2*) — Substitute the following for the existing clause:

"6.2 In respect of the requirements not covered in this standard the hexagon bolts shall comply with the requirements of IS 1367 (Part 1) : 1980 'Technical supply conditions for threaded steel fasteners : Part 1 Introduction and general information (*second revision*)'."

(*Page 3, clause 6.3*) — Substitute the following for the existing clause:

"6.3 The hexagon nuts used with the hexagon bolts shall conform to IS 1363 (Part 3) : 1984 'Hexagon head bolts, screws and nuts of product grade C : Part 3 Hexagon nuts (size range M 5 to M 36)'."

(*Page 3, clause 6.4*) — Substitute the following for the existing clause:

"6.4 The bolts shall be supplied in natural finish unless otherwise specified by the purchaser. At the request of purchaser, the bolts may be galvanized as per IS 1367 (Part 13) : 1983 'Technical supply conditions for threaded steel fasteners : Part 13 Hot-dip galvanized coatings on threaded fasteners (*second revision*)'."

(EDC 27)