

**AMENDMENT NO. 5 NOVEMBER 1999
TO
IS 6639 : 1972 SPECIFICATION FOR HEXAGON BOLTS
FOR STEEL STRUCTURES**

(*Page 3, clause 3*) — Substitute the following for the existing clause:

"3. Mechanical Properties — The mechanical properties of the hexagon bolts shall conform to the property class 4.6 or 5.6 as specified in IS 1367 (Part 3) : 1991 'Fasteners — Threaded steel — Technical supply conditions : Part 3 Mechanical properties and test methods for bolts, screws and studs with full loadability (*third revision*)'."

(*Page 3, clause 6.1*) — Substitute the following for the existing clause:

"6.1 Sampling, Inspection and Acceptance Criteria — The method of sampling, inspection and acceptance criteria shall be in accordance with IS 1367 (Part 17) : 1996 'Industrial fasteners — Threaded steel fasteners — Technical supply conditions Part : 17 Inspection, sampling and acceptance procedure'."

(*Page 3, clause 6.3*) — Substitute the following for the existing clause:

"6.3 The hexagon nuts used with the hexagon bolts shall conform to IS 1363 (Part 3) : 1992 ' Hexagon head bolts, screws and nuts of product grade C : Part 3 Hexagon nuts (size range M5 to M64) (*third revision*)'."

6.3.1 The hot-dip galvanized hexagon nuts used with the hot-dip galvanized hexagon bolts shall conform to IS 14394 : 1996 'Industrial fasteners — Hexagon nuts of product grade C — Hot-dip galvanized — Specification (size range M12 to M36)'."

(LM 14)