

AMENDMENT NO. 2 JANUARY 2006
TO
IS 6701 : 1985 SPECIFICATION FOR
TUNGSTEN FILAMENT MISCELLANEOUS
ELECTRIC LAMPS

(First Revision)

(Page 4, clause 1.1, line 3) — Add 'decorative lamps' after 'night lamps,'.

(Page 6, clause 3.3.3) — Substitute the following for the existing:

'Insulation resistance between the shell of the cap and the contacts of bayonet capped lamps, or between the shell and the insulated skirt of skirted Edison screw capped lamps, shall be not less than 2 MΩ. Insulation resistance measurements shall be carried out with suitable test equipment using a d.c. voltage of 500 V. Measurements are made on finished lamps. The lamps, if necessary, shall be aged at their rated voltage for 1 h.'

(Page 12, clause A-1.1, line 7) — Add the following after this line:

"Decorative lamps — lamp ref DL."

[Page 13, clause A-1.1, Table, row 3 (see also Amendment No. 1)] — Substitute the following for the existing:

(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)
DL & NL	230, 240, 250	15 (Max)	1322/25 × 26 or E 27/27	51	Frosted/Coloured (Inside Coated) Natural Colour & Clear	-	-	-	-

Amend No. 2 to IS 6701 : 1985

[Page 15, clause **C-2.1**, Table 1A, row 5 (see also Amendment No. 1)] —
Substitute the following for the existing:

(1)	(2)	(3)	(4)	(5)	(6)	(7)
<i>DL</i>	15 (<i>Max</i>)	-	120 (<i>Max</i>)	120 (<i>Max</i>)	120 (<i>Max</i>)	-
		-				
<i>NL</i>	15 (<i>Max</i>)		75 (<i>Max</i>)	75 (<i>Max</i>)	75 (<i>Max</i>)	-

(ET 23)