

**AMENDMENT NO. 1 SEPTEMBER 2005
TO
IS 11451 : 1986 RECOMMENDATIONS FOR
SAFETY AND HEALTH REQUIREMENTS RELATING
TO OCCUPATIONAL EXPOSURE TO ASBESTOS**

(*Page 4, clause 3.2*) — Substitute the following for the existing clause:

‘3.2 Asbestos — The fibrous form of mineral silicates belonging to the serpentine and amphibole groups of rock forming materials; under serpentine group chrysotile variety and under amphibole group crocidolite, amosite, actinolite, anthophyllite and tremolite varieties are commercially used.’

[*Page 5, clause 4.1(a)*] — Substitute the following for the existing:

‘a) For 8 hours time-weighted average (TWA), the permissible exposure limit shall be 1 fibre/cc or as stipulated by competent regulatory authority.’

[*Page 9, clause 4.2.4.3(a)*] — Substitute the following for the existing:

‘a) Every worker, irrespective of his exposure profile shall have periodic medical examination done, as recommended by regulatory authority.’

(*Page 10, clause 4.2.7*) — Substitute the following for the existing clause:

‘4.2.7 Lung Function Evaluation — The spirometer used to record FVC and FEV₁ should have a device which provides a tracing of volume-time or volume-flow curve. This tracing hard copy shall be stored and available for recall.

While recording FVC and FEV₁, the technique shall be properly demonstrated, and a minimum of three acceptable manoeuvres shall be performed, and a maximum value out of three shall be recorded.

Predicated values of lung function of that ethnic group for comparison is an approximation accepted in the absence of pre-employment and periodic medical examination observations.’

Amend No.1 to IS 14511 : 1986

(*Page 10, clause 4.2.8, second para*) — Substitute the following for the existing:

‘The records shall be maintained and stored for a period of 15 years following the termination of employment or for 40 years after first day of employment, whichever is later .’

(*Page 12, clause 4. 5.2.2*) — Substitute the following for the existing:

‘**4.5.2.2** *Sampling frequency and patterns*

Sampling frequency shall be maintained as detailed in clause **D-2.5** of IS 11450 .’

(CED 53)