

AMENDMENT NO. 1 JULY 2011
TO
IS 11462 : 1985 SPECIFICATION FOR MOULD AND
CORE SAND DRYERS, ROTARY TYPE

[Page 4, clause 1.1(c)] — Delete.

(Page 5, clause 3.8) — Substitute the following for the existing:

‘The drive system shall comprise a friction drive through rollers and tier. Rollers are made of EN-9 steel and Tier is made of mild steel. One or two of the supporting roller is/are made live driven through motor and gear box and rotates the shell by friction through supporting ring tier. The speed depends on size of rotary dryer.’

(Page 6, clause 3.9) — Delete.

(Page 7, clause 6.1, line 5) — Delete the words ‘and not less than 500°C’.

(Page 7, clause 6.4) — Substitute the following for the existing:

‘The atomizing air pressure shall depend on the burner design type and fuel to be used.’

[Page 7, clause 7.1(i)] — Substitute the following for the existing:

Fuel oil like heavy furnace oil,	9 500 kcal/kg to	0.78 to 0.96 (for liquid
light diesel oil, high speed	10 500 kcal/kg	with respect to water = 1).
diesel and LSHS fuel		Specific gravity with
		respect to water also varies
		for different fuel oil.

[Page 8, clause 7.1(iii)] — Delete and renumber the other columns.

[Page 8, clause 7.1(iv)]:

- a) Delete the words ‘(Baroda gas)’ from the first column.
- b) Substitute the following for existing in the second column:
‘8 000 – 9 000 kcal/Nm³’.
- c) Delete the words ‘(with respect to air =1)’ from the third column.

Amend No. 1 to IS 11462 : 1985

(Page 9, clause 8.1.3, Heading) — Substitute ‘*Safety of Fuel Combustion*’ for ‘*Control of Fuel Combustion*’.

[Page 10, clause 8.1.3(e)] — Add the following at the end:

f) **Gas Train Equipment** — Gas Train Equipment as safety device shall consist of the following:

- Manual shut-off valve
- Gas filter
- Gas governor
- Safety shut-off valve
- Low gas pressure switch
- High gas pressure switch
- Pressure gauge with 2-way cock

(Page 10, clause 8.1.4) — Add the following as new clause 8.1.4 and renumber the existing clause 8.1.4 as 8.1.4.1:

‘**8.1.4 Temperature Control System** — The dryer can be supplied with or without automatic temperature controlling system, which if required will consist of following:

- Thermocouple to be located in the oven
- Temperature Controller
- Combustion Air Control Valve with Actuator
- Fuel/Air Ratio Regulator

(Page 11, clause 9.2) — Add the following at the end:

‘In case of certain types fuel air burners, atomizing air pressure may be higher, say 1 300 to 1 500 mmWG and 5 to 6 bar in case of atomization with compressed air.’

(MTD 26)

Reprography Unit, BIS, New Delhi, India