

**AMENDMENT NO. 1 MARCH 1999
TO
IS 11487 : 1985 SPECIFICATION FOR SODIUM
LAURYL ETHER SULPHATE FOR COSMETIC
INDUSTRY**

[Page 4, Table 1, Sl No. (x)] — Insert Sl No. (xi) and (xii) after (x):

(1)	(2)	(3)	(4)
xi) Transmittance, percent, <i>Min</i>		85	A-13
xii) Total microbial count, cfu/ml, <i>Max</i>		1 000	(IS 14648 : 1998)

(Page 15, clause A-12.3) — Insert a new clause 'A-13' after 'A-12.3':

A-13 DETERMINATION OF TRANSMITTANCE

A-13.1 Outline of the Method — The transmittance of 50 percent aqueous solution of sodium lauryl ether sulphate is spectrophotometrically determined in 1 cm fused silica cell at 420 nm.

A-13.2 Apparatus

A-13.2.1 Spectrophotometer

A-13.2.2 Fused Silica Cells — 2, 1 cm.

A-13.3 Procedure

A-13.3.1 Spectrophotometric Measurements — Weigh accurately 50.0 ± 0.1 g of the sample, dissolved in 50 ml of distilled water and mix well. Filter the solution through Whatman filter paper to remove any undissolved foreign material. Bring the solution to room temperature and let it stand until all the air bubbles disappear. Fill one of the fused silica cells with the test solution and fill the other cell with water. Carry out the spectrophotometric measurements at 420 nm after having adjusted the instrument to 100 transmittance against water.

A-13.3.2 Correction for Transmittance of Cells — Fill the two cells used for the measurements (A-13.3.1) with distilled water and measure the transmittance of each cell at a wavelength of 420 nm. Let one of the cells read '100' since it has been used to adjust the instrument to 100 transmittance.

Amend No. 1 to IS 11487 : 1985

A-13.4 Calculation — Calculate the transmittance of aqueous solution of SLES as under:

$$\begin{array}{l} \text{Transmittance of SLES (aqueous solution)} \\ \text{in 1 cm fused silica cell at 420 nm} \end{array} = \frac{T_1 - T_0}{1}$$

where

T_1 = transmittance of test solution,

T_0 = correction for the differences in transmittance of the cells, and

l = optical path length of the cell, cm.

(PCD 19)