

Free amendment provided by BIS via BSB Edge Portal Linked to Pricing(prajwalekaradoss@gmail.com)
113.199.238.108

AMENDMENT NO. 1 JUNE 1990
TO
IS 11562:1985 SPECIFICATION FOR O-RINGS
FOR WRIST WATCH CROWNS AND PUSH BUTTONS

(Page 1, table) - Substitute ' ϕd_1 ' for ' $\phi d_1 \pm 0.05$ '
and ' ϕd_2 ' for ' $\phi d_2 \pm 0.05$ ' ± 0.1

(Page 1, clause 2) - Insert the following after the table:

'2.1 Tolerance - On ϕd_1 and ϕd_2 shall be as given in the table below:

All dimensions in millimetres.

Type	T o l e r a n c e	
	$\underline{d}_1$	$\underline{d}_2$
A	± 0.05	± 0.05
B	± 0.1	± 0.05

(Page 1, clause 3) - Substitute the following for the existing clause:

'3. Designation - O-rings for water resistant type crowns and push buttons for wrist watches shall be designated as:

Example 1 'O' rings of inner dia ring of $\underline{d}_1=1.80$ mm with a tolerance of ± 0.05 mm and cross-sectional dia $\underline{d}_2 = 0.55$ mm shall be designated as 'O' ring 1.80 X 0.55 Type / IS : 11562.

Example 2 'O' rings of inner dia ring of $d_1 = 1.80$ mm with a tolerance of $+ 0.1$ mm and cross-sectional dia $d_2 = 0.55$ mm shall be designated as 'O' ring 1.80 X 0.55 Type B IS: 11562'.

(LMD 23)

Reprography Unit, BIS, New Delhi, India