

AMENDMENT NO. 2 SEPTEMBER 1994
TO
IS 11708 : 1986 SPECIFICATION FOR HAND,
MECHANICAL

[*Page 1, clauses 2 and 2.1 (see also Amendment No. 1)*] — Substitute the following for the existing clauses:

'2 Shape and Dimensions

2.1 The general shape of the hand is shown in Fig. 1.'

(*Page 1, clause 2.1*) — Insert a new clause **2.2** as follows:

'2.2 The hand shall generally be made in two sizes, namely, small and large, or Size I and Size II. The dimensions of these sizes shall be as given in Table 1.'

[*Page 1, Table 1 (see also Amendment No. 1)*] — Substitute the following for the existing table:

TABLE 1 DIMENSIONS OF MECHANICAL HAND
(*Fig. 1 and Clause 2.2*)

Size	Length, <i>l</i>	Width, <i>w</i>
	mm	mm
(1)	(2)	(3)
I (Small)	60 ± 3	70 ± 3
II (Large)	105 ± 5	135 ± 5

NOTE 1 — All dimensions are in opponence/pinch position.

NOTE 2 — Dimensions of all fingers shall be proportionate to the overall dimensions specified.

(*Page 1, clause 3.1, second sentence*) — Delete.

(*Page 1, clause 3.3*) — Delete.

(*Page 2, clause 4.4*) — Substitute the following for the existing clause:

'4.4 The force required for just opening the hand shall be 8 N, *Min* and that for full opening the hand shall be 30 N, *Max*.'

(Page 2, clauses 5.2 and 5.3) — Delete.

(Page 2, clause 7.2) — Substitute the following for the existing clause:

‘7.2 Load Test — (Applicable to types covered under 1.1 and 1.2 only). The unit (in closed position) shall be capable of having a hook grasp of 50 N and 100 N for Size I and Size II hand respectively.’