

AMENDMENT NO. 2 APRIL 2006
TO
IS 11722 : 1986 SPECIFICATION FOR
THIN WALLED FLEXIBLE QUICK COUPLING PIPES

(Page 4, clause 2.1) — Substitute the following the existing:

‘The pipe shall be manufactured from the steel conforming to ‘O’ grade of IS 513. Pipe of nominal OD 250 and 300 mm may also be manufactured from steel conforming to IS 10748 Hot-rolled steel strip for welded tubes and pipes.’

(Page 5, clause 6.1, Table 1) — Substitute the following for the existing table:

Table 1 Sizes for Thin Walled Quick Coupling Pipes

Outside Diameter mm	Wall Thickness, mm	
	Type A ¹⁾	Type B ²⁾
25.4	—	1.40
31.8	—	1.40
38.1	—	1.40
50.8	1.00	1.60
63.5	—	1.60
76.2	1.00	1.60
101.6	1.00	1.60
127.0	1.25	1.60
152.4	1.40	1.60
203.2	—	2.00
254.0	—	2.60
304.8	—	3.10

¹⁾Pressure activated couplers.

²⁾Mechanically clamped couplers.

Amend No. 2 to IS 11722 : 1986

(*Page 6, Table 2*) — Substitute the following for the existing table:

Table 2 Maximum Permissible Leakage

Outside Diameter	Volume Per Minute
mm	ml
50.8	7
76.2	10
101.6	13
127.0	17
152.4	20

(*Page 8, clause 17.1, line 3*) — Substitute 'outside diameter' for 'nominal diameter'.

(MTD 19)

Reprography Unit, BIS, New Delhi, India