

AMENDMENT NO. 2 APRIL 2008
TO
IS 4880 (PART 5) : 1972 CODE OF PRACTICE FOR
DESIGN OF TUNNELS CONVEYING WATER

PART 5 STRUCTURAL DESIGN OF CONCRETE
LINING IN SOFT STRATA AND SOILS

(Page 22, clause B-3.1.3):

a) Substitute $P_v = \frac{B \left[\gamma - \frac{2C}{B} \right]}{2k \tan \phi} \left[1 - e^{(-2KH/B) \tan \phi} \right]$, for

$$P_v = \frac{B \left[\gamma - \frac{2C}{B} \right]}{2K \tan \phi} \left[1 - e^{-K \tan \phi \frac{2H}{B}} \right]$$

b) Substitute 'C = cohesion' for 'C = co-efficient of cohesion'.

[Page 23, clause B-4.1(c)]:

a) Substitute ' e_1 ' for ' e^1 ' and ' e_2 ' for ' e^2 '.

b) Substitute ' $e_1 = h \gamma \tan^2 (45^\circ - \phi/2) - 2C \tan (45^\circ - \phi/2)$ ' for ' $e^1 = h \tan^2 (45^\circ - \phi/2) - 2C \tan (45^\circ - \phi/2)$ '.

c) Substitute ' $e_2 = (h + m) \gamma \tan^2 (45^\circ - \phi/2) - 2C \tan (45^\circ - \phi/2)$ ' for ' $e^2 = (h + m \gamma) \tan^2 (45^\circ - \phi/2) - 2C \tan (45^\circ - \phi/2)$ '.

d) Substitute 'C = cohesion' for 'C = co-efficient of cohesion'.

(WRD 14)