

AMENDMENT NO. 1 DECEMBER 2013
TO
IS 4911 : 1986 GLOSSARY OF TERMS RELATING TO
BITUMINOUS WATERPROOFING AND
DAMP-PROOFING OF BUILDINGS

(First Revision)

[Page 5 a(5)] — Substitute the following for the existing definition:

‘*Saturated bitumen felt* — This felt is saturated with bitumen and dusted with talc or mica.’

[Page 5, a(6), line 3] — Substitute ‘talc or mica’ for ‘talc’.

[Page 5, b(2)] — Substitute the following for the existing definition:

‘*Saturated fluxed pitch felt* — This felt is saturated with crude coal tar and dusted with talc or mica.’

[Page 6, (d)] — Substitute the following for the existing definition:

‘d) *Bituminous Asbestos Felts* — In this class the base consists of a sheet of asbestos fibre and is saturated with a suitable bitumen.

1) *Saturated bituminous asbestos felt* — This felt is saturated with bitumen and dusted with talc or mica.

2) *Self Finished bituminous asbestos felt* — In which the base is coated with oxidized bitumen and surfaced on each side with a dressing of finally divided talc or mica.’

(Page 6, *Bitumen Primer*) — Substitute the following for the existing definition:

‘*Bitumen Primer* — Bitumen cutback with volatile solvent like kerosene oil, diesel and furnace oil of suitable viscosity, is applied cold over non-bituminous surface for arresting dust, filling capillary voids and for serving as a bond with the superimposed layer.’