

AMENDMENT NO. 1 NOVEMBER 1984
TO
IS : 6244-1980 SPECIFICATION FOR GAUGING MEMBERS FOR
PLAIN PLUG GAUGES GO AND NO GO MEMBERS
(SIZE RANGE ABOVE 40 TO 120 mm)
(First Revision)

Alterations

(Page 1, title) — Substitute the following for the existing title:

‘ Indian Standard

SPECIFICATION FOR GAUGING MEMBERS FOR PLAIN PLUG
GAUGES GO AND NO GO MEMBERS (SIZE RANGE ABOVE
40 UP TO AND INCLUDING 120 mm)
(First Revision) ‘

(Page 1, Table 1) — Substitute the following for the existing table :

TABLE 1 DIMENSIONS FOR GO AND NO GO GAUGING MEMBERS FOR PLAIN PLUG GAUGES (SIZE RANGE ABOVE 40 UP TO AND INCLUDING 120 mm) (Clause 3 and Fig. 1) All dimensions in millimetres.									
Nominal Diameter, d		*Handle No.	Dimensions						d ₄
Above	Up to and Including		GO			NO GO			
			L	t ₁	R ₁	L	t ₂	R ₂	
40	50	8	25	8	—	18	5	—	—
50	65	8	30	8	—	18	5	—	—
65	80	9 for GO 10 for NO GO	35	10	5	25	8	5	48
80	90		35	10	5	25	8	5	55
90	95		35	10	5	25	8	5	60
95	100		35	10	5	25	8	5	65
100	110		35	10	5	25	8	5	75
110	120		40	10	5	25	8	5	85
*IS : 5388-1983 ' Hexagon handles for plug gauges plain and threaded (second revision) '.									

(Page 3, clause 6.4, Example) — Substitute the following for the existing example:

‘ Example :

A GO gauging member for plain plug gauge to check a blind hole (BH) 50 and tolerance
class H8 shall be designated as:

GO Gauging Member BH 50 — H8 IS : 6244 ‘