

**AMENDMENT NO. 2 OCTOBER 1996  
TO  
IS 6284 : 1985 TEST CODE FOR POWER  
THRESHER FOR CEREALS**

( *Second Revision* )

( *Page 4, Fig. 1, Terms* ) — Substitute 'UPPER CONCAVE' for 'THRESHING DRUM'.

( *Page 10, clause 8.1.4, Note* ) — Delete.

[ *Page 10, clause 8.1.4.1(a)(iii)* ] — Substitute '20 seconds' for '60 seconds'.

( *Page 10, clause 8.1.4.3, Note* ) — Delete.

( *Page 11, clause 8.1.4.4, Note* ) — Delete.

( *Page 11, clause 8.1.5, Note* ) — Delete.

( *Page 13, clause 8.1.10 ( see also Amendment No. 1 )* ) — Insert the following new clauses after 8.1.10:

**'8.1.11 Determination of Corrected Output Capacity** — To avoid the variation of moisture content of grain and grain crop ratio, the output capacity as obtained under 8.1.10 should be corrected by the following formula:

$$W_1 = [ W - W ( M - m ) / 100 ] r / R$$

where

- $W_1$  = corrected output capacity,  
 $W$  = output capacity ( see 8.1.10 ),  
 $M$  = observed moisture content ( see 5.2 ),  
 $R$  = observed grain ratio in percent ( see 5.1 ), and  
 $m$  and  $r$  = constants for different crops as given in following table ( see Note ).

| Crops | $m$ | $r$ |
|-------|-----|-----|
| Wheat | 12  | 40  |
| Paddy | 20  | 40  |

NOTE — The value of  $m$  and  $r$  for other crops will be added later on.

**Amend No. 2 to IS 6284 : 1985**

**8.1.11.1** Record the data in Data Sheet as given in Appendix H.'

( *Page 14, clause 8.2* ) — Substitute the following for the existing clause:

**'8.2 Long Run Test** — Operate the thresher at least 20 hours at load for each recommended crop which should be covered by continuous run of at least 5.0 hours. Record the major breakdown, defects developed, repairs and average grain output after the test in data sheet as given in Appendix J.'

( FAD 59 )