

**AMENDMENT NO. 3 MAY 2002
TO
IS 6284 : 1985 TEST CODE FOR POWER THRESHER
FOR CEREALS**

(*Second Revision*)

(Page 9, clause 8.1.2) Delete

[Page 13, clause 8.1.11 (see also Amendment No 2)] — Substitute the following for the existing text

8.1.11 Determination of Corrected Output Capacity — To avoid the variation of moisture content of grain and grain-crop ratio, the output capacity as obtained under 8.1.10 should be corrected by the following formula

$$W_1 = \left[\frac{W r}{100} \frac{(100 - M_1)}{(100 - m_1)} + \frac{(100 - R) (1000 - M_2)}{R(100 - m_2)} \right]$$

Where

W_1 = corrected output capacity,

W = observed output capacity,

R = grain crop ratio,

M_1 and M_2 = moisture content of grain and straw respectively at observed grain-crop ratio, and

m_1 , m_2 and r = Standard moisture content of grain, straw, and standard grain-crop ratio in percent as given below

Crops	m_1	m_2	r
Wheat	9	7	40
Paddy	20	22	40
Bengal Gram	8	7	50
Sorghum (ear head)	8	9	75
Soybean	9	9	40

Amend No. 3 to IS 6284 : 1985

NOTE — Maximum moisture content of grain during threshing shall be 16 to 25 for paddy and 10 to 14 percent for other grains.

(FAD 59)