

AMENDMENT NO. 2 JUNE 1991
TO
IS 6290 : 1986 SPECIFICATION FOR STEAM IRONS
(First Revision)

(Page 4, clause **0.3**) — Insert the following clause as **0.4** after **0.3** and renumber the subsequent clause:

'0.4 Recommended temperature ranges of ironing for different types of fabrics have been given in Appendix AA.'

[Page 9, clause **18.1**, para 6, line 1 (see also Amendment No.1)] — Substitute 'Appendix **BB**' for 'Appendix **AA**'.

(Page 16, clause **101**) — Insert the following clause as **101** and renumber the subsequent clauses:

'101 MEASUREMENT OF HEATING-UP TIME

101.1 The iron is placed on the three pointed metallic supports while under measurement. The three pointed supports are constructed so that they support the sole plate of the iron horizontally at least 100 mm above the base surface on which the iron is placed. The thermocouple is attached at the mid-point of the sole plate (see Fig. 103).

101.2 Starting from ambient temperature, the iron is heated-up with the voltage corresponding to rated input, the thermostat, if any, set at the highest temperature. Where a rated voltage range is specified, this voltage should correspond to the voltage corresponding to mean rated input.

101.3 The heating-up time which is the time necessary for the temperature to exceed the ambient temperature by 180°C is measured, and is expressed in minutes and seconds.

101.4 The heating-up time shall not exceed 8 minutes.'

(Page 26, Table 101) — Substitute the table given on page 2 for the existing table:

TABLE 101 SCHEDULE OF TYPE TEST
(Clause 108.1)

SL NO.	TEST	CLAUSE REFERENCE
1.	Protection against electric shock	8
2.	Input	10
3.	Temperature-rise	11
4.	Operation under overload conditions	12
5.	Electrical insulation, and leakage current at operating temperature	13
6.	Moisture resistance	15
7.	Insulation resistance and electric strength (after humidity treatment)	16
8.	Endurance	18
9.	Abnormal operation	19
10.	Stability	20
11.	Mechanical strength	21
12.	Construction	22
13.	Cord grip and cord guard	25
14.	Earthing connection	27
15.	Screws and connections	28
16.	Creepage distances and clearances	29
17.	Resistance to heat, fire and tracking	30
18.	Resistance to rusting	31
19.	Finish	33
20.	Measurement of heating-up time	101
21.	Measurement of sole plate temperature	102
22.	Measurement of temperature distribution	103
23.	Measurement of overswing temperature and heating-up excess temperature	104
24.	Measurement of cyclic fluctuation of temperature of hottest point	105
25.	Measurement of temperature drop under load	106
26.	Measurement of heating-up time under steaming operation	107
27.	Measurement of steaming time and steaming rate	108

(Page 29, Appendix AA) — Renumber the existing Appendix as 'BB' and insert the following Appendix as 'AA':

APPENDIX AA

(Clause 0.4)

RECOMMENDED IRONING TEMPERATURE RANGES

<i>Fabric</i>	<i>(Temperature 0°C)</i>
Nylon	70 to 90
Rayon	100 to 120
Silk	130 to 150
Wool	160 to 180
Cotton/linen	190 to 210

(EID 32)