

AMENDMENT NO. 2 JULY 1975
TO
IS : 6297 (Part I)-1971 SPECIFICATION FOR
TRANSFORMERS AND INDUCTORS (POWER,
AUDIO, PULSE AND SWITCHING) FOR
ELECTRONIC EQUIPMENT
PART I GENERAL REQUIREMENTS AND TESTS

Addenda

(Page 10, clause 6.2.1.7, second paragraph) — Add the following matter after the second paragraph:

‘ The limiting current for the test equipment shall not exceed 2 mA for transformers upto 2 kVA power rating. However, any other current may be agreed upon between the manufacturer and the purchaser for transformers whose output voltage is greater than 2 800 V peak or the power rating is higher than 2 kVA. The value of the limiting current shall be included in the test report. ’

(Page 12, clause 6.2.3.2) — Add the following new clause after 6.2.3.2 and re-number the subsequent clauses and figures accordingly wherever they appear:

‘ 6.2.3.3 Centre tap balance test (for centre tapped winding) — The balance of centre tapped winding shall be checked by connecting the transformer as shown in Fig. 2.

The resistor r shall be adjusted until voltage V across the load R_L goes through minimum. The limits shall be as specified when calculated from the formula:

$$\text{Change of voltage in dB} = 20 \log_{10} \frac{R}{r-R},$$