

AMENDMENT NO. 1 SEPTEMBER 1977
TO
IS : 6580-1972 SPECIFICATION FOR
TRAIN LIGHTING BELT FASTENERS

Alterations

(*Page 3, clause 0.4*) — Substitute the following for the existing clause:

'0.4 A belt punch and cutting tool is illustrated in Appendix A.'

[*Page 4, Table 1, Sl No. (iii)*] — Substitute the following for the existing matter under the respective headings:

'iii)	Self-locking nut	a) Carbon steel	2600-1964†	B
		b) Nylon	—	—'

(*Page 5, Fig. 1, Outer Plate (with 2 holes)*] — Substitute '22.5' for '21.85'.

[*Page 5, Fig. 1, Outer Plate (with 3 holes)*] — Substitute '3R' for '3.5R'.

Addenda

(*Page 3, clause 1.1.1*) — Add the following new sentence at the end:

'Fasteners with two holes are meant for belting of 75 mm width.'

(*Page 4, clause 3.1*) — Add the following new clauses after the existing clause:

'3.2 The serrations shall be 0.7 ± 0.05 mm deep and shall be 4 mm apart. The inclination of serrations with respect to the sides of the plates shall be $45 \pm 2^\circ$ and the angle of V grooves of serrations shall be $60 \pm 2^\circ$.

3.3 The bolts and nuts shall conform to fine grade of tolerance; class 4h for bolts and class 5H for nuts as prescribed in IS : 4218 (Part IV)-1967 ISO metric screw threads: Part IV Tolerancing system.'

[*Page 5, Fig. 1, Bolt with SQ Neck (Enlarged)*] — Add '2.5 mm' as the length of square neck of bolt.

(*Page 5, Fig. 1*) — Add the following note:

'NOTE — Tolerance of ± 0.2 mm shall apply on all dimensions except where otherwise stated.'