

AMENDMENT NO. 3 DECEMBER 1998
TO
IS 675 : 1973 SPECIFICATION FOR
BUNTING, WORSTED
(Second Revision)

(Page 4, Table 1, col 2, against Variety No. 2) — Substitute '44s' for '40s/44s'.

[Page 4, Note in Table 1 (see also Amendment No. 1)] — Substitute the following for the existing:

'NOTE — Polyamide fibres may be used subject to a maximum of 15 percent in the admixture to indigenous wool at the top stage. The percentage content of wool and polyamide shall be determined in accordance with IS 2006 : 1988 'Method for quantitative chemical analysis of binary mixtures of protein fibre with certain other non-protein fibres (second revision).'

(Page 5, clause 2.2.2) — Substitute the following for the existing:

'2.2.2 The fabric shall be rendered moth-proof by using any suitable moth-proofing agent subject to prior approval of buyer. The supplier shall indicate the type of moth-proofing agent used and its concentration. He shall also give the test method for determination of the quantity of moth-proofing agent used. When new moth-proofing agent is used, besides furnishing the concentration and test method, the supplier shall also tender a certificate issued by Government authorised test bouse about the efficacy of the moth-proofing agent used and also of its being free from any undue toxicity.

If for any reason the fabric has not been rendered moth-proof, the same shall be preserved with naphthalene (see IS 539 : 1974) using a minimum quantity of 5 kg/m³ of volume of the package.'

[Page 7, Table 3, Sl No. (ii), and Amendment No. 2] — Delete the requirement and renumber the subseqent requirement.

(Page 7, Table 3) — Insert the follwing new requirement at the end of the table:

SL NO.	CHARACTERISTICS	REQUIREMENTS	METHOD OF TEST
iii)	pH of aqueous extract	5.0-7.5	IS 1390 (Cold Method)

(TX 04)